

E-180 S MX

eMTB Gravity / Enduro Suspension



Big terrain needs a big bike, the E-180 platform gives riders huge confidence and huge suspension to truck over anything on natural trails or any jump in the park - and with Bosch power it's easy to spin back up to do it all over again.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned RockShox Super Deluxe Select R and ZEB suspension
- SRAM GX Eagle drivetrain
- Code R Brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	63 +/- 0.5	75.4	609.6	345	
L	63 +/- 0.5	75.2	642.8	345	
XL	63 +/- 0.5	75	674.7	345	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1255.5	444	30.9	100	420
L	1290.8	444	30.9	115	445
XL	1324.6	444	30.9	130	470

SKU Part Code	WE180S(size)V4
Sizes Available	M,L,XL
Colour	Matt Black with Chilli & Grey
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	RockShox ZEB 29", 180mm Travel, 44mm Offset, DebonAir, Charger R Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Super Deluxe Select R, DebonAir, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 55R/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 9 deg Micro Engagement 4 Pawl, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	DT Swiss Hybrid 30, Sleeved Joint, 32 Hole
Tyres	Maxxis Assigai WT, TR, 29" x 2.5" 120TPI, EXO+ Sidewall Protection, 3C MaxxGrip, Dual Compound, Folding Bead, Front, Maxxis Assigai WT, TR, 27.5" x 2.5" 120TPI, Double Down Casing, 3C MaxxGrip, Dual Compound, Rear
Shift Levers	SRAM GX Eagle Lunar, Single Click, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle Lunar, 12 Speed
Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Whyte drop.it II Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, MMX Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code R, MMX
Pedals	None

E-180 RSX MX

eMTB Gravity / Enduro Suspension



Big terrain needs a big bike, the E-180 platform gives riders huge confidence and huge suspension to truck over anything on natural trails or any jump in the park - and with Bosch power it's easy to spin back up to do it all over again.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned Fox Factory Series suspension
- SRAM GX AXS drivetrain
- Code RSC brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	63 +/- 0.5	75.4	609.6	345	
L	63 +/- 0.5	75.2	642.8	345	
XL	63 +/- 0.5	75	674.7	345	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1255.5	444	30.9	100	420
L	1290.8	444	30.9	115	445
XL	1324.6	444	30.9	130	470

SKU Part Code	WE180RS(size)V4
Sizes Available	M,L,XL
Colour	Matt Black with Burnt Orange & Gold
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	Fox Float 38, Factory 29", 180mm Travel, 44mm Offset with Grip 2 Damper and custom tune, Tapered Steerer, Kashima Coating, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float X2, Factory, independently adjustable Compression and Rebound damping, Kashima coating
Headset	FSA No. 55/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Stainless Steel Bearings, 12mm x 148mm Boost, XD Driver, 32 Hole
Front Hub	Hope Pro 4, Stainless Steel Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	Black Sapim Race stainless steel double butted spokes built with silver brass nipples
Rims	Hope Fortus 30, Tubless Ready, 32 Hole
Tyres	Maxxis Assigai WT, TR, 29" x 2.5" 120TPI, EXO + Sidewall Protection, 3C MaxxGrip, Dual Compound, Folding Bead, Front, Maxxis Assigai WT, TR, 27.5" x 2.5" 120TPI, Double Down Casing, 3C MaxxGrip, Dual Compound, Rear
Shift Levers	SRAM AXS Rocker Paddle, MMX, Eagle 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X01 Eagle AXS 12 Speed, with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	Race Face Affect E-Bike, 165mm, ISIS with X-SYNC Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, M/L 150mm Travel, XL 170mm Travel, High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Race Face Turbine R, 35mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Race Face Atlas, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code RSC, MMX
Pedals	None

E-180 WORKS

eMTB Gravity / Enduro Suspension



Big terrain needs a big bike, the E-180 platform gives riders huge confidence and huge suspension to truck over anything on natural trails or any jump in the park - and with Bosch power it's easy to spin back up to do it all over again.

Key Spec

- E BIKE SYSTEM - UNDER EMBARGO
- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned RockShox Super Deluxe Ultimate and ZEB Ultimate suspension
- SRAM XX1 AXS drivetrain
- Code RSC Brakes

e-Bike Information	
Drive Unit	UNDER EMBARGO
Battery	UNDER EMBARGO
Battery Charger	UNDER EMBARGO
Display	UNDER EMBARGO

Suspension Information	
Shock Stroke & Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	63 +/- 0.5	75.4	609.6	345	
L	63 +/- 0.5	75.2	642.8	345	
XL	63 +/- 0.5	75	674.7	345	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1255.5	444	30.9	100	420
L	1290.8	444	30.9	115	445
XL	1324.6	444	30.9	130	470

SKU Part Code	WE180W(size)V1
Sizes Available	M,L,XL
Colour	Gloss White with Black
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	RockShox ZEB Ultimate 29", 180mm Travel, 44mm Offset, DebonAir, Charger 2.1 RC2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Stealth
Rear Shock	RockShox Super Deluxe Ultimate RCT, Air, Fast Black Coating, Adjustable Rebound, low speed compression adjustment and tuneable DebonAir
Headset	FSA No. 55R/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Stainless Steel Bearings, 12mm x 148mm Boost, XD Driver, 32 Hole
Front Hub	Hope Pro 4, Stainless Steel Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	Black Sapim Race stainless steel double butted spokes built with silver brass nipples
Rims	Hope Fortus 30, Tubless Ready, 32 Hole
Tyres	Maxxis Assgail WT, TR, 29" x 2.5" 120TPI, EXO + Sidewall Protection, 3C MaxxGrip, Dual Compound, Folding Bead, Front, Maxxis Assgail WT, TR, 27.5" x 2.5" 120TPI, Double Down Casing, 3C Maxx Grip, Dual Compound, Rear
Shift Levers	SRAM AXS Rocker Paddle, MMX, Eagle 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XX1 Eagle AXS 12 Speed, with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	Race Face Affect E-Bike, 165mm, ISIS with X-SYNC Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, M/L 150mm Travel, XL 170mm Travel, High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Race Face Turbine R, 35mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Race Face Atlas, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 220mm Disc
Brake Levers	SRAM Code RSC, MMX
Pedals	None

E-160 S (27.5" sizes XS & S)

eMTB Trail / Enduro Suspension



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned RockShox Deluxe Select R and ZEB suspension
- Shimano XT LinkGlide drivetrain
- TRP Trail Evo Brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	64	76.12	547	342.7	
S	64.5 +/- 0.5	75.7	571.4	342.7	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1181.2	444	30.9	120	360
S	1200.4	444	30.9	130	395

SKU Part Code	WE160S(size)V3
Sizes Available	XS,S
Colour	Gloss Turquoise with Black & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	RockShox ZEB 27.5", 160mm Travel, 44mm Offset, DebonAir, Charger R Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + R, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 55R/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assgial WT, TR, 27.5" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 27.5" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	Shimano M8130 Deore XT 11 speed
Front Derailleur	N/A
Rear Derailleur	Shimano M8130 Deore XT, Shadow Plus, direct mount
Cassette	Shimano CS-LG600, 11 speed, 11-50T
Chain	Shimano CN-LG500, 11 speed
Crankset	Whyte, Forged Alloy, 165mm, direct mount 36T
Bottom Bracket	N/A
Seatpost	Whyte drop.it Adjust, 30.9mm, XS/S 120-150mm Travel, M/L 140-170mm Travel, XL 170-200mm Travel, MMX Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	TRP Trail Evo, 5mm Hose, 4 Piston Caliper with Sintered Metal Pads, 220mm 2.3mm Disc
Rear Brakes	TRP Trail Evo, 5mm Hose, 4 Piston Caliper with Sintered Metal Pads, 203mm 2.3mm Disc
Brake Levers	TRP Trail Evo
Pedals	None

E-160 S (MX - sizes M, L & XL)

eMTB Trail / Enduro Suspension



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned RockShox Deluxe Select R and ZEB suspension
- Shimano XT LinkGlide drivetrain
- TRP Trail Evo Brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

SKU Part Code	WE160S(size)V3
Sizes Available	M,L,XL
Colour	Gloss Turquoise with Black & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	RockShox ZEB 29", 160mm Travel, 44mm Offset, DebonAir, Rush RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select R, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 55R/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assgial WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 27.5" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	Shimano M8130 Deore XT 11 speed
Front Derailleur	N/A
Rear Derailleur	Shimano M8130 Deore XT, Shadow Plus, direct mount
Cassette	Shimano CS-LG600, 11 speed, 11-50T
Chain	Shimano CN-LG500, 11 speed
Crankset	Whyte, Forged Alloy, 165mm, direct mount 36T
Bottom Bracket	N/A
Seatpost	Whyte drop.it Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	TRP Trail Evo, 5mm Hose, 4 Piston Caliper with Sintered Metal Pads, 220mm 2.3mm Disc
Rear Brakes	TRP Trail Evo, 5mm Hose, 4 Piston Caliper with Sintered Metal Pads, 203mm 2.3mm Disc
Brake Levers	TRP Trail Evo
Pedals	None

E-160 RS (27.5" size S)

eMTB Trail / Enduro Suspension

Colour Option 1



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned Fox Performance suspension
- SRAM GX AXS drivetrain
- Code R brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5 +/- 0.5	75.7	571.4	342.7	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1200.4	444	30.9	130	395

SKU Part Code	WE160RS1SV3-1
Sizes Available	S
Colour	Matt Black with Lime & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	Fox Float 38, Performance 27.5", 160mm Travel, 44mm Offset with Grip Damper, 3pos Adjust, Tapered Steerer, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float Performance DPS, Evol LV, Custom tuned for Whyte, 3pos adjustable Compression and Rebound damping
Headset	FSA No. 55/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assigai WT, TR, 27.5" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR WT, TR, 27.5" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button MMX
Front Derailleur	N/A
Rear Derailleur	SRAM GX1 AXS Lunar with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, XS/S 125mm Travel, High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code R, MMX
Pedals	None

E-160 RS (MX - sizes M, L & XL)

eMTB Trail / Enduro Suspension

Colour Option 1



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned Fox Performance suspension
- SRAM GX AXS drivetrain
- Code R brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

SKU Part Code	WE160RS(size)V3-1
Sizes Available	M,L,XL
Colour	Matt Black with Lime & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	Fox Float 38, Performance 29", 160mm Travel, 44mm Offset with Grip Damper, 3pos Adjust, Tapered Steerer, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float Performance DPS, Evol LV, Custom tuned for Whyte, 3pos adjustable Compression and Rebound damping
Headset	FSA No. 55/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assigai WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 27.5" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button MMX
Front Derailleur	N/A
Rear Derailleur	SRAM GX1 AXS Lunar with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, M/L 150mm, XL 170mm Travel, High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code R, MMX
Pedals	None

E-160 RS (27.5" size S)

eMTB Trail / Enduro Suspension

Colour Option 2



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned Fox Performance suspension
- SRAM GX AXS drivetrain
- Code R brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5 +/- 0.5	75.7	571.4	342.7	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1200.4	444	30.9	130	395

SKU Part Code	WE160RS1SV3-2
Sizes Available	S
Colour	Gloss Lime with Black & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	Fox Float 38, Performance 27.5", 160mm Travel, 44mm Offset with Grip Damper, 3pos Adjust, Tapered Steerer, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float Performance DPS, Evol LV, Custom tuned for Whyte, 3pos adjustable Compression and Rebound damping
Headset	FSA No. 55/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assigai WT, TR, 27.5" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR WT, TR, 27.5" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button MMX
Front Derailleur	N/A
Rear Derailleur	SRAM GX1 AXS Lunar with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, XS/S 125mm Travel, High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code R, MMX
Pedals	None

E-160 RS (MX - sizes M, L & XL)

eMTB Trail / Enduro Suspension

Colour Option 2



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned Fox Performance suspension
- SRAM GX AXS drivetrain
- Code R brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

SKU Part Code	WE160RS(size)V3-2
Sizes Available	M,L,XL
Colour	Gloss Lime with Black & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	Fox Float 38, Performance 29", 160mm Travel, 44mm Offset with Grip Damper, 3pos Adjust, Tapered Steerer, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float Performance DPS, Evol LV, Custom tuned for Whyte, 3pos adjustable Compression and Rebound damping
Headset	FSA No. 55/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assigai WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 27.5" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button MMX
Front Derailleur	N/A
Rear Derailleur	SRAM GX1 AXS Lunar with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, M/L 150mm, XL 170mm Travel, High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code R, MMX
Pedals	None

E-160 S 29er

eMTB Trail / Enduro Suspension

Colour Option 1



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned RockShox Deluxe Select R and ZEB suspension
- SRAM GX Eagle drivetrain
- Guide RE Brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	64.5 +/- 0.5	75.5	607.3	340	
L	64.5 +/- 0.5	75.3	640.4	340	
XL	64.5 +/- 0.5	75.1	672.5	340	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1234.8	446	30.9	105	420
L	1269.2	446	30.9	120	445
XL	1302.7	446	30.9	135	470

SKU Part Code	WE160ST(size)V1-1
Sizes Available	M,L,XL
Colour	Matt Black with Turquoise & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	RockShox ZEB 29", 160mm Travel, 44mm Offset, DebonAir, Rush RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select R, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 55R/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assgial WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 29" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX Eagle Lunar, Single Click, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle Lunar, 12 Speed
Cassette	SRAM PG1210, 11-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Whyte drop.it Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, MMX Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Guide RE, MMX
Pedals	None

E-160 S 29er

eMTB Trail / Enduro Suspension

Colour Option 2



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned RockShox Deluxe Select R and ZEB suspension
- SRAM GX Eagle drivetrain
- Guide RE Brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	64.5 +/- 0.5	75.5	607.3	340	
L	64.5 +/- 0.5	75.3	640.4	340	
XL	64.5 +/- 0.5	75.1	672.5	340	

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1234.8	446	30.9	105	420
L	1269.2	446	30.9	120	445
XL	1302.7	446	30.9	135	470

SKU Part Code	WE160ST(size)V1-2
Sizes Available	M,L,XL
Colour	Gloss Turquoise with Black & White
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	RockShox ZEB 29", 160mm Travel, 44mm Offset, DebonAir, Rush RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select R, Fast Black Coating, Adjustable Rebound
Headset	FSA No. 55R/35 Orbit 1.5 ZS, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole
Tyres	Maxxis Assgial WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 29" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX Eagle Lunar, Single Click, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle Lunar, 12 Speed
Cassette	SRAM PG1210, 11-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Whyte drop.it Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, MMX Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Guide RE, MMX
Pedals	None

E-160 RSX 29er

eMTB Trail / Enduro Suspension

Colour Option 1



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned Fox Performance Elite suspension
- SRAM GX AXS drivetrain
- Code RSC brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	64.5 +/- 0.5	75.5	607.3	340	
L	64.5 +/- 0.5	75.3	640.4	340	
XL	64.5 +/- 0.5	75.1	672.5	340	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1234.8	446	30.9	105	420
L	1269.2	446	30.9	120	445
XL	1302.7	446	30.9	135	470

SKU Part Code	WE160RSXT(size)V1-1
Sizes Available	M,L,XL
Colour	Matt Black with Burnt Orange & Gold
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	Fox Float 38, Performance Elite 29", 160mm Travel, 44mm Offset with Grip 2 Damper, Tapered Steerer, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float X Performance Elite DPS, Evol LV, Custom tuned for Whyte
Headset	FSA No. 55/35 Orbit 1.5 Z5, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Stainless Steel Bearings, 12mm x 148mm Boost, XD Driver, 32 Hole
Front Hub	Hope Pro 4, Stainless Steel Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	Black Sapim Race stainless steel double butted spokes built with silver brass nipples
Rims	Hope Fortus 30, Tubless Ready, 32 Hole
Tyres	Maxxis Assgigai WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 29" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button MMX
Front Derailleur	N/A
Rear Derailleur	SRAM GX1 AXS Lunar with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, M/L 150mm, XL 170mm Travel. High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code RSC, MMX
Pedals	None

E-160 RSX 29er

eMTB Trail / Enduro Suspension

Colour Option 2



The new E-160 platform combines Bosch reliability with Whyte custom tuned suspension for maximum confidence in rough and steep terrain and raucous pop and flick agility for very rider on every ride.

Key Spec

- Bosch CX Smart System with 750WH battery and new LED remote controller
- Exclusive Whyte custom-tuned Fox Performance Elite suspension
- SRAM GX AXS drivetrain
- Code RSC brakes

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT750 Horizontal
Battery Charger	4A (230V)
Display	Bosch LED Remote

Suspension Information	
Shock Stroke & Sag Setting	57.5mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	64.5 +/- 0.5	75.5	607.3	340	
L	64.5 +/- 0.5	75.3	640.4	340	
XL	64.5 +/- 0.5	75.1	672.5	340	
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1234.8	446	30.9	105	420
L	1269.2	446	30.9	120	445
XL	1302.7	446	30.9	135	470

SKU Part Code	WE160RSXT(size)V1-2
Sizes Available	M,L,XL
Colour	Gloss Orange with Black & Gold
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape.it Link and 12mm X 148mm Boost Dropouts
Fork	Fox Float 38, Performance Elite 29", 160mm Travel, 44mm Offset with Grip 2 Damper, Tapered Steerer, 110mm x 15mm Boost, E-Thru Axle
Rear Shock	Fox Float X Performance Elite DPS, Evol LV, Custom tuned for Whyte
Headset	FSA No. 55/35 Orbit 1.5 Z5, 1.8" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Stainless Steel Bearings, 12mm x 148mm Boost, XD Driver, 32 Hole
Front Hub	Hope Pro 4, Stainless Steel Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	Black Sapim Race stainless steel double butted spokes built with silver brass nipples
Rims	Hope Fortus 30, Tubless Ready, 32 Hole
Tyres	Maxxis Assgigai WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 29" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button MMX
Front Derailleur	N/A
Rear Derailleur	SRAM GX1 AXS Lunar with Battery Protector
Cassette	SRAM XG-1275 Eagle, 10-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Crank Bro High-Line 3, 30.9mm, M/L 150mm, XL 170mm Travel. High-Line Ball Socket Remote Lever
Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code RSC, MMX
Pedals	None

G-180 S MX

Gravity Full Suspension



Awaiting photography - mock up to show colourway

From Enduro winning race runs to back flips over Darkfest jumps, the big hitting G-180 has you and the trail covered - its time to trust and just send it.

Key Spec

- RockShox Zeb Base Forks
- RockShox Deluxe Select + Rear Shock
- SRAM SX Mechanical Gearing
- SRAM Guide RE Brakes

Suspension Information	
Shock Stroke & Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

SKU Part Code	WG180S(size)V3
Sizes Available	S,M,L,XL
Colour	Gloss Bronze with Gold & Heather
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox ZEB 29", 180mm Travel, 44mm Offset, DebonAir, Rush RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment
Headset	FSA No. 57 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Assegai WT, TR, 29" x 2.5" 120TPI, EXO+ Sidewall Protection, 3C MaxxGrip, Dual Compound, Folding Bead, Front, Maxxis Minion DHR II WT, TR, 27.5" x 2.4" WT 120TPI, Double Down Casing, 3C MaxxTerra, Rear
Shift Levers	SRAM SX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX Eagle, 12 Speed
Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed
Chain	SRAM Eagle, 12 Speed
Crankset	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 165mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it II Adjust, 30.9mm, S/M/L 140-170mm Travel, XL 170-200mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 20mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Guide RE, MMX
Pedals	None

G-180 RS MX

Gravity Full Suspension



From Enduro winning race runs to back flips over Darkfest jumps, the big hitting G-180 has you and the trail covered - its time to trust and just send it.

Key Spec

- RockShox Zeb Base Forks
- RockShox Super Deluxe Select + Rear Shock
- SRAM GX Mechanical Gearing
- SRAM Code R Brakes

Suspension Information	
Shock Stroke & Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

SKU Part Code	WG180RS(size)V3
Sizes Available	S,M,L,XL
Colour	Matt Diesel with Light Blue & Slate
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox ZEB Select + 29", 180mm Travel, 44mm Offset, DebonAir, Charger 2.1 RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Super Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment
Headset	FSA No. 57 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 9 deg Micro Engagement 4 Pawl, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss Factory 2.0mm, Black Stainless, Brass Nipples
Rims	Race Face 27.5" rear, 29" front AR-30, Offset, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Assegai WT, TR, 29" x 2.5" 60TPI, EXO+ Sidewall Protection, 3C Maxx Grip, Dual Compound, Folding Bead, Front, Maxxis Minion DHR WT, TR, 27.5" x 2.4" WT 120TPI, Double Down Casing, 3C Maxx Terra, Rear
Shift Levers	SRAM GX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-52, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM Descendant 7K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Bike Yoke Divine, 30.9mm, M/L/XL 160mm Travel, Triggy Remote with MMX attachment
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 20mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc, Internal Routing
Brake Levers	SRAM Code R, MMX
Pedals	None

G-180 WORKS 29er

Gravity Full Suspension



From Enduro winning race runs to back flips over Darkfest jumps, the big hitting G-180 has you and the trail covered - its time to trust and just send it.

Key Spec

- RockShox Zeb Ultimate Forks
- RockShox Super Deluxe Ultimate Rear Shock
- SRAM XX1 & X01 AXS Electronic Gearing
- SRAM Code R Brakes

Suspension Information	
Shock Stroke & Sag Setting	65mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	230mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	64.3 (63.7)	75.6	605.3	349 (340.9)	839
L	64.3 (63.7)	75.3	638.9	349 (340.9)	844
XL	64.3 (63.7)	75.1	671.4	349 (340.9)	861

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1241	440	30.9	100	431.8
L	1275	440	30.9	115	457.2
XL	1309	440	30.9	130	482.6

SKU Part Code	WG180W(size)V3
Sizes Available	M,L,XL
Colour	Matt Granite with Chalk & Mist
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox ZEB Ultimate 29", 180mm Travel, 44mm Offset, DebonAir, Charger 2.1 RC2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Stealth
Rear Shock	RockShox Super Deluxe Ultimate RCT, Air, Fast Black Coating, Adjustable Rebound, low speed compression adjustment and tuneable DebonAir
Headset	FSA No. 57 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Hope Pro 4, Stainless Steel Bearings, 12mm x 148mm Boost, XD Driver, 32 Hole
Front Hub	Hope Pro 4, Stainless Steel Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	Black Sapim Race stainless steel double butted spokes built with silver brass nipples
Rims	Hope Fortus 30, Tubless Ready, 32 Hole
Tyres	Maxxis Assegai WT, TR, 29" x 2.5" 120TPI, EXO+ Sidewall Protection, 3C Maxx Grip, Dual Compound, Folding Bead, Front, Maxxis Minion DHR II WT, TR, 29" x 2.4" 120TPI, Double Down Casing, 3C Maxx Terra, Rear
Shift Levers	SRAM AXS Rocker Paddle, MMX, 12 speed
Front Derailleur	N/A
Rear Derailleur	SRAM X01 Eagle AXS, 12 Speed
Cassette	SRAM XG-1299 Eagle, 10-52, 12 Speed, Rainbow
Chain	SRAM XX1 Eagle, 12 Speed, Rainbow
Crankset	SRAM Descendant Carbon, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	RockShox Reverb Stealth, 30.9mm, M/L 175mm Travel, XL 200mm Travel, X1 Remote
Seat	Whyte Custom, Team, Lightweight Foam, CrMo Rails
Bar	Race Face NEXT R Carbon, 20mm Rise, 35mm Bar Bore, 800mm Wide
Stem	Race Face Atlas, 35mm Bar Bore, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 220mm Disc
Rear Brakes	SRAM Code RSC, 4 Piston with Sintered Metal Pads, 200mm Disc, Internal Routing
Brake Levers	SRAM Code RSC, MMX
Pedals	None

T-160 S

Enduro Full Suspension



Blurring the lines between Enduro and Trail the T-160 is such a capable machine, making this platform perfect for riders who want an epic ride one day, and a winch and plummet play day the next

Key Spec

- RockShox Lyrik Base Forks
- RockShox Deluxe Select + Rear Shock
- Shimano Deore 12 speed Mechanical Gearing
- TRP Trail Evo Brakes

Suspension Information	
Shock Stroke & Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	64.7 (64.1)	75.1	606	345 (337)	825
L	64.7 (64.1)	74.8	640	345 (337)	828
XL	64.7 (64.1)	74.6	672	345 (337)	839
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1222	440	30.9	110	431.8
L	1256	440	30.9	125	457.2
XL	1290	440	30.9	140	482.6

SKU Part Code	WT160S(size)V3
Sizes Available	M,L,XL
Colour	Gloss Cement with Rose & Slate
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Lyrik 29", 160mm Travel, 44mm Offset, DebonAir+, Rush RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Assegai TR 29" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Minion DHR II TR 29" x 2.4" WT 120TPI, EXO+ Sidewall Protection, Dual Compound, Rear
Shift Levers	Shimano M6100Deore, I-Spec EV, 12 speed,
Front Derailleur	N/A
Rear Derailleur	Shimano M6100 Deore, SGS, Shadow Plus, 12 speed
Cassette	Sunrace CSMZ901, 11-51, Black, 12 speed
Chain	Shimano M6100, 12 speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount alloy 32T Narrow wide Chaining, 170mm, Boost, 12 speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte drop.it Post II Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, Shimano Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 20mm Rise, 31.8mm, 800mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	TRP Trail Evo, 4 Piston with Sintered Metal Pads, 203mm 2.3mm Disc
Rear Brakes	TRP Trail Evo, 4 Piston with Sintered Metal Pads, 203mm 2.3mm Disc
Brake Levers	TRP Trail Evo
Pedals	None

T-160 RSX

Enduro Full Suspension



Blurring the lines between Enduro and Trail the T-160 is such a capable machine, making this platform perfect for riders who want an epic ride one day, and a winch and plummet play day the next

Key Spec

- RockShox Lyrik Ultimate Forks
- RockShox Super Deluxe Ultimate Rear Shock
- SRAM GX AXS Electronic Gearing
- SRAM Code R Brakes

Suspension Information	
Shock Stroke & Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	64.7 (64.1)	75.1	606	345 (337)	825
L	64.7 (64.1)	74.8	640	345 (337)	828
XL	64.7 (64.1)	74.6	672	345 (337)	839
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1222	440	30.9	110	431.8
L	1256	440	30.9	125	457.2
XL	1290	440	30.9	140	482.6

SKU Part Code	WT160RSX(size)V3
Sizes Available	M,L,XL
Colour	Matt Moss with Willow Green & Dark Olive
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Lyrik Ultimate RC2 29"; 160mm Travel, 44mm Offset, DebonAir, Charger 2.1 RC2 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Super Deluxe Ultimate RCT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 9 deg Micro Engagement 4 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	Race Face AR-30, Offset, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Assegai TR 29" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Minion DHR II TR 29" x 2.4" WT 120TPI, EXO+ Sidewall Protection, Dual Compound, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX AXS Lunar Eagle, with Battery Protector, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-52, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM GX Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it Post II Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, MMX Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 20mm Rise, 31.8mm, 800mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc
Rear Brakes	SRAM Code R, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Code R, MMX
Pedals	None

T-140 SR

Trail Full Suspension



Our shortest travel bike, but that doesn't make it any less capable. From down-country to bike parks the T-140 will show you the true meaning of mountain biking – to have fun.

Key Spec

- RockShox Pike Base Forks
- RockShox Deluxe Select + Rear Shock
- Shimano Deore 11 speed Mechanical Gearing
- TRP Slate Evo Brakes

Suspension Information	
Shock Stroke & Sag Setting	50mm, Sag 13mm (25%) to 16mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	65.9 (65.3)	74.9	555	330.1 (322.3)	788
S	65.9 (65.3)	74.7	583	330.1 (322.3)	796
M	65.9 (65.3)	74.5	612	330.1 (322.3)	802
L	65.9 (65.3)	74.3	640	330.1 (322.3)	808
XL	65.9 (65.3)	74.1	669	330.1 (322.3)	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1139	435	30.9	100	368.3
S	1168	435	30.9	112	406.4
M	1198	435	30.9	125	431.8
L	1228	435	30.9	140	457.2
XL	1256	435	30.9	150	482.6

SKU Part Code	WT140SR(size)V3
Sizes Available	XS,S,M,L,XL
Colour	Matt Diesel with Light Blue & Slate
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip Seat Clamp System, ISCG, 2 Bolt Guide Mounts, Alloy Symmetrical SCR Rear Triangle, 148mm Boost Dropouts
Fork	Rock Shox Pike, 27.5", 40mm Travel, 37mm Offset, Debonair+, Rush Damper, Fast Black Coating, Tapered Steerer, 110 x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, Centre Lock 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 27.5" x 2.6" 120TPI, EXO+ Sidewall Protection, 3C Maxx Terra, Rear
Shift Levers	Shimano Deore M5100, I-Spec EV 11 Speed, Black
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5100-SGS, Shadow Plus, 11 Speed
Cassette	SunRace CSMS8, 11-51, 11 Speed
Chain	KMC X11 Black/Silver, 11 Speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount alloy 32T Narrow Wide Boost Chaining, 170mm, Boost, 11 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	KS 900I, 30.9mm, XS 100mm, S 125mm, M/L/XL 150mm Travel, Shimano Post Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 31.8mm, XS/S 15mm Rise, 760mm Wide, M/L/XL, 30mm Rise 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	TRP Slate Evo, 4 Piston with Sintered Metal Pad, 180mm 2.3mm Disc
Rear Brakes	TRP Slate Evo, 4 Piston with Sintered Metal Pad, 180mm 2.3mm Disc, Internal Routing
Brake Levers	TRP Slate Evo
Pedals	None

T-140 S

Trail Full Suspension



Our shortest travel bike, but that doesn't make it any less capable. From down-country to bike parks the T-140 will show you the true meaning of mountain biking – to have fun.

Key Spec

- RockShox Pike Base Forks
- RockShox Deluxe Select + Rear Shock
- SRAM GX Mechanical Gearing
- SRAM G2 R Brakes

Suspension Information	
Shock Stroke & Sag Setting	50mm, Sag 13mm (25%) to 16mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.9 (65.3)	74.7	583	330.1 (322.3)	796
M	65.9 (65.3)	74.5	612	330.1 (322.3)	802
L	65.9 (65.3)	74.3	640	330.1 (322.3)	808
XL	65.9 (65.3)	74.1	669	330.1 (322.3)	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1168	435	30.9	112	406.4
M	1198	435	30.9	125	431.8
L	1228	435	30.9	140	457.2
XL	1256	435	30.9	150	482.6

SKU Part Code	WT140S(size)V3
Sizes Available	S,M,L,XL
Colour	Matt Moss with Dark Olive & Burnt Orange
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Pike 27.5", 140mm Travel, 37mm Offset, DebonAir, R Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, Centrelock, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, Centrelock, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 27.5" x 2.6" 120TPI, EXO+ Sidewall Protection, Rear
Shift Levers	SRAM GX Lunar Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Lunar Eagle, 12 Speed
Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it II Adjust, 30.9mm, S/M 120-150mm Travel, L/XL 140-170mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 31.8mm, 5 15mm Rise, 760mm Wide, M/L/XL, 30mm Rise 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc, Internal Routing
Brake Levers	SRAM Guide G2 R, Matchmaker
Pedals	None

T-140C R

Trail Full Suspension



Our shortest travel bike, but that doesn't make it any less capable. From down-country to bike parks the T-140 will show you the true meaning of mountain biking – to have fun. Adding a Whyte carbon frame turns the entertainment up to 11

Key Spec

- RockShox Pike Select + Forks
- RockShox Deluxe Select + Rear Shock
- SRAM GX Eagle Mechanical Gearing
- SRAM G2 R Brakes

Suspension Information	
Shock Stroke & Sag Setting	50mm, Sag 13mm (25%) to 16mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.9 (65.3)	74.7	583	330.1 (322.3)	796
M	65.9 (65.3)	74.5	612	330.1 (322.3)	802
L	65.9 (65.3)	74.3	640	330.1 (322.3)	808
XL	65.9 (65.3)	74.1	669	330.1 (322.3)	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1168	435	30.9	112	406.4
M	1198	435	30.9	125	431.8
L	1228	435	30.9	140	457.2
XL	1256	435	30.9	150	482.6

SKU Part Code	WT140CR(size)V3
Sizes Available	S,M,L,XL
Colour	Matt Olive with Black & Gold
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, ISCG, 2 Bolt Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Pike Select RC 27.5"; 140mm Travel, 37mm Offset, DebonAir, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 42 Orbit Z5 Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 27.5" x 2.6" 120TPI, EXO+ Sidewall Protection, 3C Maxx Terra, Rear
Shift Levers	SRAM GX Eagle Lunar, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle Lunar, 12 Speed
Cassette	SRAM PG- 1230 Eagle, 11-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it II Adjust, 30.9mm, S/M 120-150mm Travel, L/XL 140-170mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 31.8mm, S 15mm Rise, 760mm Wide, M/L/XL, 30mm Rise 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc, Internal Routing
Brake Levers	SRAM Guide G2 R, Matchmaker
Pedals	None

T-140C RSX

Trail Full Suspension



Our shortest travel bike, but that doesn't make it any less capable. From down-country to bike parks the T-140 will show you the true meaning of mountain biking – to have fun. Adding a Whyte carbon frame turns the entertainment up to 11

Key Spec

- RockShox Pike Ultimate Forks
- RockShox Deluxe Ultimate Rear Shock
- SRAM GX Eagle AXS Electronic Gearing
- SRAM G2 RS Brakes

Suspension Information	
Shock Stroke & Sag Setting	50mm, Sag 13mm (25%) to 16mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.9 (65.3)	74.7	583	330.1 (322.3)	796
M	65.9 (65.3)	74.5	612	330.1 (322.3)	802
L	65.9 (65.3)	74.3	640	330.1 (322.3)	808
XL	65.9 (65.3)	74.1	669	330.1 (322.3)	815

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1168	435	30.9	112	406.4
M	1198	435	30.9	125	431.8
L	1228	435	30.9	140	457.2
XL	1256	435	30.9	150	482.6

SKU Part Code	WT140CRSX(size)V3
Sizes Available	S,M,L,XL
Colour	Matt Zinc with Black & Grey
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, ISCG, 2 Bolt Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Pike Ultimate RC 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger RCT3 Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Ultimate RCT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 42 Orbit Z5 Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 9 deg Micro Engagement 4 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	Race Face AR-30, Offset, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 27.5" x 2.6" 120TPI, EXO+ Sidewall Protection, 3C Maxx Terra, Rear
Shift Levers	SRAM GX AXS Eagle, 2 Button, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle AXS Lunar, with Battery Protector, 12 Speed
Cassette	SRAM XG-1275 Eagle, 10-52, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM GX Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Bike Yoke Revive, 30.9mm, S 125mm Travel, M/L/XL 160mm Travel, Triggly Remote with MMX attachment
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte G061 Alloy, 31.8mm, S 15mm Rise, 760mm Wide, M/L/XL, 30mm Rise 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide G2 RS, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide G2 RS, 4 Piston, 180mm Disc, Internal Routing
Brake Levers	SRAM Guide G2 RS, MMX
Pedals	None

T-140 S 29er

Trail Full Suspension



Full fun meets full speed with the all-new T-140 29er platform. With custom-tuned suspension and our proprietary Total Geometry, benchmark Whyte handling is guaranteed - from down-country adventures to your favourite trails.

Key Spec

- RockShox Pike Select Forks
- RockShox Deluxe Select + Rear Shock
- Shimano Deore 12 speed Mechanical Gearing
- TRP Slate Evo Brakes

Suspension Information	
Shock Stroke & Sag Setting	47.5mm, Sag 12m (25%) to 15mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65.3 (64.7)	76.4	575	338.1 (330)	735
M	65.3 (64.7)	76.2	603.9	338.1 (330)	735
L	65.3 (64.7)	76	636.6	338.1 (330)	735
XL	65.3 (64.7)	75.8	667.7	338.1 (330)	735

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1184.7	435	30.9	107	395
M	1215.1	435	30.9	120	420
L	1249.5	435	30.9	135	445
XL	1282	435	30.9	148	470

SKU Part Code	WT140ST(size)V2
Sizes Available	S,M,L,XL
Colour	Matt Moss with Chalk & Dark Olive
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Pike Select 29", 140mm Travel, 44mm Offset, DebonAir+, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF TR 29" x 2.5" WT 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 29" x 2.4" WT 60TPI, EXO+ Sidewall Protection, 3C Maxx Terra, Rear
Shift Levers	Shimano Deore M6100, I-Spec EV, 12 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M6100, Shadow Plus, 12 Speed
Cassette	Sunrace CSMZ901, 11-51T, Black
Chain	Shimano Deore M6100, 12 Speed
Crankset	Whyte Forged 2pcs, Direct Mount Alloy 32T Narrow Wide Chaining, 170mm, Boost, 12 speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte drop.it Post II Adjust, 30.9mm, S 120-150mm, M/L 140-170mm Travel, XL 170-200mm Travel, Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 31.8mm, S/M 20mm Rise, L/XL, 30mm Rise 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	TRP Slate Evo, 4 Piston with Metal Pads, 180mm 2.3mm Disc
Rear Brakes	TRP Slate Evo, 4 Piston with Metal Pads, 180mm 2.3mm Disc
Brake Levers	TRP Slate Evo
Pedals	None

T-140 RSX 29er

Trail Full Suspension



Full fun meets full speed with the all-new T-140 29er platform. With custom-tuned suspension and our proprietary Total Geometry, benchmark Whyte handling is guaranteed - from down-country adventures to your favourite trails.

Key Spec

- Fox 34 Float Performance Elite Series Forks
- Fox Flat DPS Performance Elite Series Rear Shock
- SRAM GX Mechanical Gearing
- SRAM G2 R Brakes

Suspension Information	
Shock Stroke & Sag Setting	47.5mm, Sag 12m (25%) to 15mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	65.3 (64.7)	76.2	603.9	338.1 (330)	735
L	65.3 (64.7)	76	636.6	338.1 (330)	735
XL	65.3 (64.7)	75.8	667.7	338.1 (330)	735
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1215.1	435	30.9	120	420
L	1249.5	435	30.9	135	445
XL	1282	435	30.9	148	470

SKU Part Code	WT140RSXT(size)V2
Sizes Available	M,L,XL
Colour	Matt Diesel with Slate & Light Blue
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	Fox Float 34 Performance Elite 29", 140mm Travel, 44mm Offset, Grip 2 Damper, Tapered Steerer, 110mm x 15mm Boost E-Thru Axle
Rear Shock	Fox DPS Performance Elite, Evol LV, Adjustable Rebound and 3 Position Compression
Headset	FSA No. 57 Orbit ZS, ACB, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 9 deg Micro Engagement 4 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	Race Face AR-30, Offset, 30mm Wide, Sleeved Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF TR 29" x 2.5" WT 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 29" x 2.4" WT 120TPI, EXO+ Sidewall Protection, 3C Maxx Terra, Rear
Shift Levers	SRAM GX AXS Eagle 2 Button, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX AXS Lunar Eagle, with Battery Protector, 12 Speed
Cassette	SRAM PG-1275 Eagle, 11-52, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte Drop.It II, 30.9mm, Adjust, M 120-150mm, L 140-170mm, XL 170-200mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 31.8mm, 780mm Wide, M 20mm, L/XL 30mm Rise
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc, Internal Routing
Brake Levers	SRAM Guide G2 R, Matchmaker
Pedals	None

E-504

e-Hardtail MTB



Whyte knows about hardtail geometry. The E-500 Series takes all that and integrates a Bosch system to give a wide range of everyday use, from trail shredding to commuting - or both in one day.

Key Spec

- Bosch CX (Gen4) with 500WH battery and Purion Display
- RockShox 35 Silver Forks
- SRAM GX 11 speed drivetrain
- Tektro Orion Brakes
- KS 900i Dropper post

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT500 Horizontal
Battery Charger	2A (100-240V)
Display	Bosch Purion Performance Line

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	64	74.5	569	305	788
S	64.5	74.5	590	305	794
M	64.5	74.5	620	305	805

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1146	440	30.9	107	381
S	1163	440	30.9	115	406
M	1193	440	30.9	115	444

SKU Part Code	WE504(size)V1
Sizes Available	XS,S,M
Colour	Matt Diesel with Light Blue & Slate
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox 35 Silver TK 27.5"; 120mm Travel, 37mm Offset, Fast Black Coating, Adjustable Compression and Rebound, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit Z5, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster TR 27.5" x 2.6" 60TPI, EXO Sidewall Protection
Shift Levers	SRAM GX, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed
Cassette	SRAM PG-1130, 11-42, 11 Speed
Chain	KMC NPBK Sport, 11 Speed
Crankset	Whyte, Steel narrow/wide, 165mm, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	KS 900i, 150mm Travel, 30.9 x 445mm, with Southpaw Alloy Remote
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, XS & S 760mm Wide, M 780mm Wide
Stem	Whyte Alloy 6061, 45mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Orion, 4-Piston with Sintered Metal Pads, 200mm Disc, Post Mount
Rear Brakes	Tektro Orion, 4-Piston with Sintered Metal Pads, 200mm Disc, Post Mount, Internal Routing
Brake Levers	Tektro Orion
Pedals	None

E-505

e-Hardtail MTB



Whyte knows about hardtail geometry. The E-500 Series takes all that and integrates a Bosch system to give a wide range of everyday use, from trail shredding to commuting - or both in one day.

Key Spec

- Bosch CX (Gen4) with 500WH battery and Purion Display
- RockShox 35 Silver Forks
- SRAM GX 11 speed drivetrain
- Tektro Orion Brakes
- KS 900i Dropper post

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT500 Horizontal
Battery Charger	2A (100-240V)
Display	Bosch Purion Performance Line

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	65.5	74.5	626	305	825
L	65.5	74.5	645	305	844
XL	65.5	74.5	663	305	851

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1198	450	30.9	115	444.5
L	1217	450	30.9	125	495.7
XL	1237	450	30.9	135	533.4

SKU Part Code	WE505(size)V1
Sizes Available	M,L,XL
Colour	Matt Black with Grey & Rose
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox 35 Silver TK 29", 120mm Travel, 44mm Offset, Fast Black Coating, Adjustable Compression and Rebound, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit Z5, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster TR 29" x 2.6" 60TPI, EXO Sidewall Protection
Shift Levers	SRAM GX, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX, 11 Speed
Cassette	SRAM PG-1130, 11-42, 11 Speed
Chain	KMC NPBK Sport, 11 Speed
Crankset	Whyte, Steel narrow/wide, 165mm, Direct Mount 36T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	KS 900i 30.9, 150mm Travel, Alloy Southpaw Remote
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Alloy 6061, 45mm Extension
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro Orion, 4-Piston with Sintered Metal Pads, 203mm Disc, Post Mount
Rear Brakes	Tektro Orion, 4-Piston with Sintered Metal Pads, 203mm Disc, Post Mount, Internal Routing
Brake Levers	Tektro Orion
Pedals	None

E-506

e-Hardtail SUV



Commuting in comfort is what's needed to get more people out of cars and onto bikes. The E-506 takes MTB derived comfort and adds Bosch power, mudguards, rack and lights - perfect for every adventure to, from and after work.

Key Spec

- Bosch CX (Gen4) with 500WH battery and Purion Display
- RockShox 35 Silver Forks
- Shimano Deore 10 speed drivetrain
- Tektro Orion Brakes
- KS 900i Dropper post

e-Bike Information	
Drive Unit	Bosch Performance Line CX (25km/h) 85Nm
Battery	Bosch Power Tube PT500 Horizontal
Battery Charger	2A (100-240V)
Display	Bosch Purion Performance Line

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	74.5	601	303	788
M	64.5	74.5	629	303	795
L	64.5	74.5	653	303	801
XL	64.5	74.5	681	303	808
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	64.5	74.5	601	303	788
M	64.5	74.5	629	303	795
L	64.5	74.5	653	303	801
XL	64.5	74.5	681	303	808

SKU Part Code	WE506(size)V2-1
Sizes Available	S,M,L,XL
Colour	Matt Black with Ocean & Burnt Orange
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox 35 Silver R 27.5", 120mm Travel, 37mm Offset, Coil, Fast Black Coating, Adjustable Rebound, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Schwalbe, Super Moto-X, 27.5" x 2.4, Greenguard Puncture Protection
Shift Levers	Shimano M5130 Deore 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano M5130 Deore, GS, 10 Speed
Cassette	Shimano CS-LG600, 10 Speed, 11-43
Chain	Shimano CN-LG500, 10 Speed
Crankset	Whyte, Steel narrow/wide, 160mm, Direct Mount 38T for Bosch Performance Line CX, Black
Bottom Bracket	N/A
Seatpost	Whyte drop.it, 30.9, S 125mm, M/L/XL 150mm Travel, Paddle Remote Lever
Seat	Whyte Custom, SUV Comfort sport, Single panel, with moulded rear handle
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 720mm Wide
Stem	Whyte Alloy 6061, 60mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro Orion, 4-Piston with Sintered Metal Pads, 203mm Disc, Post Mount
Rear Brakes	Tektro Orion, 4-Piston with Sintered Metal Pads, 203mm Disc, Post Mount, Internal Routing
Brake Levers	Tektro Orion
Pedals	None

429

Trail Hardtails 29ers



Our 29er hardtails combine speed with precise and composed handling for some of the most fun you can have on 2 wheels – the 629 rated 10/10 by MBR magazine in Feb 22 for its addictive ways.

Key Spec

- RockShox Judy Coil 120mm Forks
- Shimano Deore 10 speed Mechanical Gearing
- Tektro M275 Brakes
- Maxxis Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	66.5	74.5	628	300	819
L	66.5	74.5	648	300	840
XL	66.5	74.5	665	300	864
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1177	435	30.9	115	444.5
L	1197	435	30.9	120	495.7
XL	1217	435	30.9	135	533.4

SKU Part Code	W429(size)V2
Sizes Available	M,L,XL
Colour	Matt Moss with Olive & Burnt Orange
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
Fork	RockShox Silver TK 29", 120mm Travel, Fast Black Coating, Adjustable Rebound, Turn Key Lockout
Rear Shock	N/A
Headset	FEIMIN H868B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless Compatible, 32 Hole
Tyres	MAXXIS Forekaster 29" x 2.35" Front, MAXXIS Recon Race 29" x 2.25" Rear Wire Bead
Shift Levers	Shimano Deore SL-M4010, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5020-SGS, Shadow Plus, 10 Speed /Microshift RD-M665M, With Clutch, 10 Speed
Cassette	SunRace CSMS2, ED Black, 11-46, 10 Speed
Chain	SunRace, 10 Speed
Crankset	Whyte, Forged 2pcs Cranks, 32T Narrow/Wide Chainring, 170mm, 10 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 760mm Wide
Stem	Whyte Alloy, S 35mm, M/L/XL 45mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, Hydraulic, 180mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 180mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

529

Trail Hardtails 29ers



Our 29er hardtails combine speed with precise and composed handling for some of the most fun you can have on 2 wheels – the 629 rated 10/10 by MBR magazine in Feb 22 for its addictive ways.

Key Spec

- RockShox Recon RL Air Forks
- SRAM SX 12 Speed Eagle Mechanical Gearing
- Tektro M535 Brakes
- KS 900i Dropper post

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	65	74.5	610	300	791
M	65	74.5	639	300	805
L	65	74.5	663	300	819
XL	65	74.5	690	300	838
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1185	450	30.9	110	406
M	1215	450	30.9	115	431
L	1240	450	30.9	120	457
XL	1270	450	30.9	135	483

SKU Part Code	W529(size)V5
Sizes Available	S,M,L,XL
Colour	Gloss Cement with Rose & Slate
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX63, Chainstay Post Mount Dropouts and 12mm X 148mm Boost Dropouts
Fork	RockShox Recon RL 29", 120mm Travel, 42mm Offset, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit Z5, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i27 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Ardent 29"x 2.4" EXO Dual Compound, 60TPI, Tanwall
Shift Levers	SRAM SX Eagle
Front Derailleur	N/A
Rear Derailleur	SRAM SX Eagle, 12 Speed
Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed
Chain	SRAM SX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS, 30.9mm, 5 125mm Travel, M/L/XL 150mm Travel, Paddle Remote Lever
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Alloy, 45mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	Tektro HD-M535, 4 Piston, 2.3mm gauge 180mm Disc
Rear Brakes	Tektro HD-M535, 4 Piston, 2.3mm gauge 180mm Disc, Internal Routing
Brake Levers	Tektro M-535
Pedals	Fibre Reinforced Composite Platform

629

Trail Hardtails 29ers



"Ultimately the Whyte 629 V4 is balanced, composed, stable and precise, and whether you're a relative beginner, or an experienced trail rider, you'll instantly become addicted to its ways..." 10/10 mbr Feb 2022

Key Spec

- RockShox 35 Gold Fork
- SRAM NX 12 Speed Eagle Mechanical Gearing
- SRAM Guide T Brakes
- Whyte (JD) adjustable Dropper Post

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	65	74.5	639	300	805
L	65	74.5	663	300	819
XL	65	74.5	690	300	838
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1215	450	30.9	115	431
L	1240	450	30.9	120	457
XL	1270	450	30.9	135	483

SKU Part Code	W629(size)V5
Sizes Available	M,L,XL
Colour	Matt Moss with Heather & Gold
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Internal Cable Routing with BBX63, Chainstay Post Mount Dropouts and 12mm X 148mm Boost Dropouts
Fork	RockShox 35 Gold RL 29", 120mm Travel, 44mm Offset, DebonAir, Fast Black Coating, Adjustable Compression and Rebound, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit Z5, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i27 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 29" x 2.3" 3C MaxTerra Exo Front, Maxxis Forecaster 29" x 2.35" Exo Dual compound Rear
Shift Levers	SRAM NX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX Eagle, 12 Speed
Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed
Chain	SRAM NX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte Drop.it., 30.9mm, M 150mm, L/XL 170mm Travel, South Paw MMX Remote Lever
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Alloy, 45mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide T, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide T, 4 Piston, 180mm Disc, Internal Routing
Brake Levers	SRAM Guide T, Matchmaker
Pedals	Fibre Reinforced Composite Platform

901

Enduro Hardtail



The 900 series have won more tests and reviews than we can count. Giving the rider perfect control, grip and confidence they set the benchmark for rowdy fun thanks to the perfect combination of geometry, components and tyre choice.

Key Spec

- RockShox 35 Gold Fork
- SRAM SX 12 Speed Eagle Mechanical Gearing
- TRP Slate Evo Brakes
- KS Rage-i Dropper Post

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	64.5	74.5	584	297.5	764
S	64.5	74.5	600	297.5	783
M	64.5	74.5	627	297.5	800
L	64.5	74.5	654	297.5	817
XL	64.5	74.5	682	297.5	834
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1153	440	30.9	105	381
S	1173	440	30.9	120	406.2
M	1203	440	30.9	130	431
L	1228	440	30.9	140	457
XL	1258	440	30.9	150	483

SKU Part Code	W901(size)V5
Sizes Available	XS,S,M,L,XL
Colour	Satin Bronze with Gold & Heather
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal BBX63 Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox 35 Gold RL 27.5", 130mm Travel, 37mm Offset, DebonAir, Fast Black Coating, Adjustable Compression and Rebound, Tapered Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i35 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.8" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.8" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM SX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM SX Eagle, 12 Speed
Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed
Chain	SRAM SX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	KS RAGEi, 30.9mm, XS 125mm Travel, S/M 150mm, L/XL 170mm Travel, KS South Paw MMX Remote Lever
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	TRP Slate Evo, 4 Piston with Sintered Metal Pad, 180mm Disc
Rear Brakes	TRP Slate Evo, 4 Piston with Sintered Metal Pad, 180mm Disc, Internal Routing
Brake Levers	TRP Slate Evo
Pedals	None

905

Enduro Hardtail



The 900 series have won more tests and reviews than we can count. Giving the rider perfect control, grip and confidence they set the benchmark for rowdy fun thanks to the perfect combination of geometry, components and tyre choice.

Key Spec

- RockShox Pike Select Fork
- SRAM NX 12 Speed Eagle Mechanical Gearing
- SRAM Guide T Brakes
- Whyte (JD) adjustable Dropper Post

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	74.5	600	297.5	783
M	64.5	74.5	627	297.5	800
L	64.5	74.5	654	297.5	817
XL	64.5	74.5	682	297.5	834
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1173	440	30.9	120	406.2
M	1203	440	30.9	130	431
L	1228	440	30.9	140	457
XL	1258	440	30.9	150	483

SKU Part Code	W905(size)V5
Sizes Available	S,M,L,XL
Colour	Gloss Cement with Rose & Slate
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal BBX63 Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox Pike Select RC 27.5"; 130mm Travel, 37mm Offset, DebonAir, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i35 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.8" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.8" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM NX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM NX Eagle, 12 Speed
Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed
Chain	SRAM NX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte Drop.it, 30.9mm, S/M 150mm, L/XL 170mm Travel, Paddle MMX Remote Lever
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide T, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide T, 4 Piston, 180mm Disc
Brake Levers	SRAM Guide T, Matchmaker
Pedals	None

909 X

Enduro Hardtail



The 900 series have won more tests and reviews than we can count. Giving the rider perfect control, grip and confidence they set the benchmark for rowdy fun thanks to the perfect combination of geometry, components and tyre choice.

Key Spec

- RockShox Pike Ultimate Fork
- SRAM GX AXS Electronic Gearing
- SRAM G2 R Brakes
- Whyte (JD) adjustable Dropper Post

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	74.5	600	297.5	783
M	64.5	74.5	627	297.5	800
L	64.5	74.5	654	297.5	817
XL	64.5	74.5	682	297.5	834
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1173	440	30.9	120	406.2
M	1203	440	30.9	130	431
L	1228	440	30.9	140	457
XL	1258	440	30.9	150	483

SKU Part Code	W909X(size)V5
Sizes Available	S,M,L,XL
Colour	Matt Zinc with Black & Rose
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal BBX63 Cable Routing for Dropper Post and 12mm X 148mm Boost Dropouts
Fork	RockShox Pike Ultimate 27.5", 130mm Travel, 37mm Offset, DebonAir, Charger RT3C Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	N/A
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, Micro Engagement 4 Pawl, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i35 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5" x 2.8" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Rekon TR 27.5" x 2.8" 60TPI, EXO Sidewall Protection, Rear
Shift Levers	SRAM GX AXS Eagle 2 Button, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX1 AXS Lunar Eagle with Battery Protector, 12 Speed
Cassette	SRAM XG 1275 Eagle, 10-52, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM GX Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte Drop.it, 30.9mm, S/M 150mm, L/XL 170mm Travel, Paddle MMX Remote Lever
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc
Brake Levers	SRAM Guide G2 R, MMX
Pedals	None

801

Sport Hardtail



Our highly evolved 800 Series frames feature custom seat and chain stays combined with the latest Whyte Total Geometry to provide exceptional handling, balance and control for a dynamic and super agile ride.

Key Spec

- RockShox Recon RL Air Forks
- Shimano Deore 10 speed Mechanical Gearing
- Tektro Auriga M280 Brakes
- Maxxis Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	74.5	599	303.5	780
M	64.5	74.5	627	303.5	802
L	64.5	74.5	650	303.5	826
XL	64.5	74.5	678	303.5	855
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1171	440	30.9	115	406
M	1201	440	30.9	125	444
L	1226	440	30.9	135	482.6
XL	1256	440	30.9	145	533

SKU Part Code	W801(size)V4
Sizes Available	S,M,L,XL
Colour	Matt Granite with Chalk & Rose
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX63 and Chainstay Post Mount Dropouts 12mm X 148mm Boost
Fork	RockShox Recon RL 27.5"; 120mm Travel, 37mm Offset, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	Stainless Steel 14G Black
Rims	WTB ST i27 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster 27.5"x 2.35" Dual Compound, 60TPI
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5120-SGS, Shadow Plus, 10 Speed
Cassette	SunRace CSMS2, ED Black, 11-46, 10 Speed
Chain	KMC X10 Black/Silver
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount 32T Narrow/Wide Chaining, 170mm, 10 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, S 760mm Wide, M/L/XL 780mm Wide
Stem	Whyte Alloy, 40mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	Tektro Auriga HD-M280, 180mm Disc
Rear Brakes	Tektro Auriga HD-M280, 180mm Disc, 180mm Disc, Internal Routing
Brake Levers	Tektro Auriga HD-M280
Pedals	Fibre Reinforced Composite Platform

802 Compact Sport Hardtail



Our highly evolved 800 Series frames feature custom seat and chain stays combined with the latest Whyte Total Geometry to provide exceptional handling, balance and control for a dynamic and super agile ride.

Key Spec

- RockShox Recon RL Air Forks
- Shimano Deore 10 speed Mechanical Gearing
- Tektro Auriga M280 Brakes
- Maxxis Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	64.5	74.5	580	303.5	761
S	64.5	74.5	599	303.5	779
M	64.5	74.5	618	303.5	803
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1141	440	30.9	107	381
S	1161	440	30.9	115	406
M	1191	440	30.9	125	444

SKU Part Code	W802(size)V4
Sizes Available	XS,S,M
Colour	Matt Diesel with Light Blue & Magenta
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX63 and Chainstay Post Mount Dropouts 12mm X 148mm Boost
Fork	RockShox Recon RL 27.5"; 120mm Travel, 37mm Offset, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	Stainless Steel 14G Black
Rims	WTB ST i27 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Forekaster 27.5"x 2.35" Dual Compound, 60TPI
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5120-SGS, Shadow Plus, 10 Speed
Cassette	SunRace CSMS2, ED Black, 11-46, 10 Speed
Chain	KMC X10 Black/Silver
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount 32T Narrow/Wide Chaining, 170mm, 10 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, 760mm Wide
Stem	Whyte Alloy, 45mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	Tektro Auriga HD-M280, 180mm Disc
Rear Brakes	Tektro Auriga HD-M280, 180mm Disc, 180mm Disc, Internal Routing
Brake Levers	Tektro Auriga HD-M280
Pedals	Fibre Reinforced Composite Platform

805

Sport Hardtail



Our highly evolved 800 Series frames feature custom seat and chain stays combined with the latest Whyte Total Geometry to provide exceptional handling, balance and control for a dynamic and super agile ride.

Key Spec

- RockShox Recon RL Air Forks
- Shimano Deore 11 speed Mechanical Gearing
- Tektro M535 Brakes
- KS 900i Dropper post

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	64.5	74.5	599	303.5	780
M	64.5	74.5	627	303.5	802
L	64.5	74.5	650	303.5	826
XL	64.5	74.5	678	303.5	855
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1171	440	30.9	115	406
M	1201	440	30.9	125	444
L	1226	440	30.9	135	482.6
XL	1256	440	30.9	145	533

SKU Part Code	W805(size)V4
Sizes Available	S,M,L,XL
Colour	Matt Moss with Yellow & Khaki
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX63 and Chainstay Post Mount Dropouts 12mm X 148mm Boost
Fork	RockShox Recon RL 27.5"; 120mm Travel, 37mm Offset, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i27 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis High Roller II TR 27.5"x 2.4" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Forecaster TR 27.5" x 2.35" 60TPI, EXO Sidewall Protection, Dual Compound, Rear
Shift Levers	Shimano Deore SL-M5100, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5100-5GS, Shadow Plus, 11 Speed
Cassette	SunRace CSMS8, ED Black, 11-51, 11 Speed
Chain	KMC NPBK 11 Speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount 32T Narrow/Wide Chaining, 170mm, 11 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	KS, 30.9mm, S/M 125mm, L/XL 150mm Travel, Alloy Remote Lever
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, S 760mm Wide, M/L/XL 780mm Wide
Stem	Whyte Alloy, 45mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	Tektro HD-M535, 4 Piston, 180mm, 2.3mm gauge, 180mm Disc
Rear Brakes	Tektro HD-M535, 4 Piston, 180mm, 2.3mm gauge, 180mm Disc, Internal Routing
Brake Levers	Tektro HD-M535
Pedals	Fibre Reinforced Composite Platform

806 Compact Sport Hardtail



Our highly evolved 800 Series frames feature custom seat and chain stays combined with the latest Whyte Total Geometry to provide exceptional handling, balance and control for a dynamic and super agile ride.

Key Spec

- RockShox Recon RL Air Forks
- Shimano Deore 11 speed Mechanical Gearing
- Tektro M535 Brakes
- KS 900i Dropper post

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	64.5	74.5	580	303.5	761
S	64.5	74.5	599	303.5	779
M	64.5	74.5	618	303.5	803
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1141	440	30.9	107	381
S	1161	440	30.9	115	406
M	1191	440	30.9	125	444

SKU Part Code	W806(size)V4
Sizes Available	XS,S,M
Colour	Matt Burnt Orange with Corn & Slate
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Headtube, Get A Grip Seat Clamp System, Internal Cable Routing with BBX63 and Chainstay Post Mount Dropouts 12mm X 148mm Boost
Fork	RockShox Recon RL 27.5"; 120mm Travel, 37mm Offset, Solo Air, Fast Black Coating, Adjustable Rebound, Tapered Alloy Steerer, 110mm x 15mm Boost, Maxle Lite
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Caged Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i27 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Ardent TR 27.5"x 2.4" 60TPI, EXO Sidewall Protection
Shift Levers	Shimano Deore SL-M5100, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5100-SGS, Shadow Plus, 11 Speed
Cassette	SunRace CSMS8, ED Black, 11-51, 11 Speed
Chain	KMC NPBK 11 Speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount 32T Narrow/Wide Chaining, 170mm, 11 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	KS, 30.9mm, XS/S 125mm, M 150mm Travel, Alloy Remote Lever
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 15mm Rise, 31.8mm, XS 760mm Wide, S/M 780mm Wide
Stem	Whyte Alloy, 45mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	Tektro HD-M535, 4 Piston, 180mm, 2.3mm gauge, 180mm Disc
Rear Brakes	Tektro HD-M535, 4 Piston, 180mm, 2.3mm gauge, 180mm Disc, Internal Routing
Brake Levers	Tektro HD-M535
Pedals	Fibre Reinforced Composite Platform

603

Sport Hardtail



Our 600 series models combine a best in class frame (featuring a tapered headtube and fork) with Whyte Total Geometry for maximum off-road control and stability - and a ride performance way beyond the supposed limits of a mid-priced hardtail.

Key Spec

- Suntour XCR Coil 120mm Forks
- Microshift 1x9 speed Mechanical Gearing
- Tektro M275 Brakes
- Maxxis Tyres

SKU Part Code	W603(size)V4
Sizes Available	S,M,L,XL
Colour	Gloss Cement with Burnt Orange & Slate
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
Fork	SR Suntour XCR-LO 27.5", 120mm Travel, Tapered Steerer, Hydro Lockout, Fixed Rebound Damping, Black Stanchions
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless compatible, 32 Hole
Tyres	MAXXIS Forekaster 27.5" x 2.35" Front, MAXXIS Recon Race 27.5" x 2.25" Rear Wire Bead
Shift Levers	Microshift SL-M819R, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M6195M, With Clutch, 9 Speed
Cassette	Microshift CS-H093, 11-46, 9 Speed
Chain	SunRace, 9 Speed
Crankset	Prowheel, Alloy, 3pcs Cranks Single Narrow Wide, 32T
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 760mm Wide
Stem	Whyte Alloy, S 35mm, M/L/XL 45mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, Hydraulic, 180mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	780
M	66.5	74	623	303.5	802
L	66.5	74	641	303.5	826
XL	66.5	74	660	303.5	864
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1188	435	30.9	135	482.6
XL	1208	435	30.9	145	533

604 Compact Sport Hardtail



Our 600 series models combine a best in class frame (featuring a tapered headtube and fork) with Whyte Total Geometry for maximum off-road control and stability - and a ride performance way beyond the supposed limits of a mid-priced hardtail.

Key Spec

- Suntour XCR Coil 120mm Forks
- Microshift 1x9 speed Mechanical Gearing
- Tektro M275 Brakes
- Maxxis Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	66.5	74	580	303.5	761
S	66.5	74	599	303.5	779
M	66.5	74	618	303.5	803
L	66.5	74	636	303.5	826
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1123	435	30.9	107	381
S	1143	435	30.9	115	406
M	1163	435	30.9	125	444
L	1183	435	30.9	135	482.6

SKU Part Code	W604(size)V4
Sizes Available	XS,S,M,L
Colour	Matt Diesel with Light Blue & Slate
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
Fork	SR Suntour XCR-LO 27.5", 120mm Travel, Tapered Steerer, Hydro Lockout, Fixed Rebound Damping, Black Stanchions
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless Compatible, 32 Hole
Tyres	MAXXIS Forekaster 27.5" x 2.35" Front, MAXXIS Recon Race 27.5" x 2.25" Rear Wire Bead
Shift Levers	Microshift SL-M819R, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M6195M, With Clutch, 9 Speed
Cassette	Microshift CS-H093, 11-46, 9 Speed
Chain	SunRace, 9 Speed
Crankset	Prowheel, Alloy, 3pcs Cranks Single Narrow Wide, 32T
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 740mm Wide
Stem	Whyte Alloy, XS/S 35mm, M 45mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, Hydraulic, 180mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

605

Sport Hardtail



Our 600 series models combine a best in class frame (featuring a tapered headtube and fork) with Whyte Total Geometry for maximum off-road control and stability - and a ride performance way beyond the supposed limits of a mid-priced hardtail.

Key Spec

- RockShox Judy Coil 120mm Forks
- Shimano Deore 10 speed Mechanical Gearing
- Tektro M275 Brakes
- Maxxis Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	780
M	66.5	74	623	303.5	802
L	66.5	74	641	303.5	826
XL	66.5	74	660	303.5	864
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1188	435	30.9	135	482.6
XL	1208	435	30.9	145	533

SKU Part Code	W605(size)V4
Sizes Available	S,M,L,XL
Colour	Matt Moss with Chalk & Ocean
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts
Fork	RockShox Judy TK 27.5", 120mm Travel, Adjustable Rebound, Turn Key Lockout
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Upper 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless Compatible, 32 Hole
Tyres	MAXXIS Forekaster 27.5" x 2.35" Front, MAXXIS Recon Race 27.5" x 2.25" Rear Wire Bead
Shift Levers	Shimano Deore SL-M4010, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5020-SGS, Shadow Plus, 10 Speed /Microshift RD-M665M, With Clutch, 10 Speed
Cassette	SunRace CSMS2, ED Black, 11-46, 10 Speed
Chain	SunRace, 10 Speed
Crankset	Whyte, Forged 2pcs Cranks, 32T Narrow/Wide Chainring, 170mm, 10 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 760mm Wide
Stem	Whyte Alloy, S 35mm, M/L/XL 45mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, Hydraulic, 180mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

202 20" Junior Trail



For the junior rider that wants the same uncompromising ride as their parents we use extra-fat tyres that can be run at lower pressures to give grip and comfort – way better than cheap and heavy suspension forks.

Key Spec

- Light Weight Alloy Frame and Fork
- SRAM 7 speed Gearing
- Tektro Mechanical disc brakes
- Kenda Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
11"	67	77	450	238	555
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
11"	922	365	27.2	100	280

SKU Part Code	W202V1
Sizes Available	11"
Colour	Matt Diesel with Light Blue & Mint
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX, IS Mount Dropouts
Fork	Whyte, 6061 Alloy, Rigid 20" Jr, IS Disc Mount
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail-202, 28 Hole
Tyres	KENDA K-RAD 20" x 2.3"
Shift Levers	SRAM X4 Trigger, 7-SPEED
Front Derailleur	N/A
Rear Derailleur	SRAM X4 Medium Cage, 7 speed
Cassette	SunRace 7 Speed, 13-34T
Chain	SunRace, 7 Speed
Crankset	Alloy 6061, 28T Narrow Wide Chainring, Double Guard, 127mm Crank Length
Bottom Bracket	JIS Square Interface, Cartridge Bearings
Seatpost	Whyte Jr, 6061 Alloy, Single Bolt, 27.2x250mm
Seat	Whyte Jr Custom
Bar	Whyte 6061, Riser Bar, 31.8mm, 600mm Wide
Stem	Whyte Alloy, 35mm
Grips	Whyte Custom
Front Brakes	Tektro MD-M280, Cable, 160mm Rotor
Rear Brakes	Tektro MD-M280, Cable, 140mm Rotor, Internal Routing
Brake Levers	Tektro JL352-RS, Adjustable Short Reach
Pedals	Jr Fibre Reinforced Composite Platform

302 24"

Junior Trail



For the junior rider that wants the same uncompromising ride as their parents we use extra-fat tyres that can be run at lower pressures to give grip and comfort – way better than cheap and heavy suspension forks.

Key Spec

- Light Weight Alloy Frame and Fork
- SRAM 7 speed Gearing
- Tektro Mechanical disc brakes
- Kenda Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
12"	67	75.5	497	265	627
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
12"	1005	417	27.2	100	305

SKU Part Code	W302V1
Sizes Available	12"
Colour	Matt Burnt Orange with Bone & Earth
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX, IS Mount Dropouts
Fork	Whyte, 6061 Alloy, Rigid 24" Jr, IS disc mount
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail-302, 28 Hole
Tyres	KENDA K-RAD 24" x 2.3"
Shift Levers	SRAM X4 Trigger, 7-SPEED
Front Derailleur	N/A
Rear Derailleur	SRAM X4 Medium Cage, 7 speed
Cassette	SunRace 7 Speed, 13-34T
Chain	SunRace, 7 Speed
Crankset	Alloy 6061, 28T Narrow Wide Chainring, Double Guard, 140mm Crank Length
Bottom Bracket	JIS Square Interface, Cartridge Bearings
Seatpost	Whyte Jr, 6061 Alloy, Single Bolt, 27.2x250mm
Seat	Whyte Jr Custom
Bar	Whyte 6061, Riser Bar, 31.8mm, 620mm Wide
Stem	Whyte Alloy, 35mm
Grips	Whyte Custom
Front Brakes	Tektro MD-M280, Cable, 160mm Rotor
Rear Brakes	Tektro MD-M280, Cable, 160mm Rotor, Internal Routing
Brake Levers	Tektro JL352-RS, Adjustable Short Reach
Pedals	Jr Fibre Reinforced Composite Platform

403 26"
Junior Trail
 Colour Option 1



Using the award winning 900 series as a base, the 400 series youth bikes take Total Geometry to the younger rider and give them what they need to become the very best.

Key Spec

- Suntour XCR 100 Air suspension
- Shimano Altus 9 Speed Gearing
- Tektro hydraulic disc brakes
- Vee Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	66.5	76	520	295	706
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1057	410	30.9	95	331

SKU Part Code	W403V3-1
Sizes Available	13"
Colour	Matt Granite with Grey & Mist
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	SR Suntour XCR, 100mm Travel, Hydro Lock-out, Air Spring, Adjustable Rebound, Post Mount
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail-403, 28 Hole
Tyres	VEE TIRE Co, Crown Gem 26" x 2.25"
Shift Levers	Microshift SL-M859-R, Trigger Shifter, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M46S, 9 Speed
Cassette	SunRace CSM90, ED Black 11-36, 9 Speed
Chain	SunRace, 9 Speed
Crankset	Alloy 6061, 30T Narrow Wide Chaining, Single guard, 152mm Crank Length
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 300mm, 2 Bolt Clamp
Seat	Whyte Jr Mid Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 660mm Wide
Stem	Whyte Alloy, 35mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

403 26"
Junior Trail
 Colour Option 2



Using the award winning 900 series as a base, the 400 series youth bikes take Total Geometry to the younger rider and give them what they need to become the very best.

Key Spec

- Suntour XCR 100 Air suspension
- Shimano Altus 9 Speed Gearing
- Tektro hydraulic disc brakes
- Vee Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	66.5	76	520	295	706
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1057	410	30.9	95	331

SKU Part Code	W403V3-2
Sizes Available	13"
Colour	Gloss Cement with Khaki & Sand
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	SR Suntour XCR, 100mm Travel, Hydro Lock-out, Air Spring, Adjustable Rebound, Post Mount
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail-403, 28 Hole
Tyres	VEE TIRE Co, Crown Gem 26" x 2.25"
Shift Levers	Microshift SL-M859-R, Trigger Shifter, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M46S, 9 Speed
Cassette	SunRace CSM90, ED Black 11-36, 9 Speed
Chain	SunRace, 9 Speed
Crankset	Alloy 6061, 30T Narrow Wide Chaining, Single guard, 152mm Crank Length
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm x 300mm, 2 Bolt Clamp
Seat	Whyte Jr Mid Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 660mm Wide
Stem	Whyte Alloy, 35mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

405 26"

Junior Trail



Using the award winning 900 series as a base, the 400 series youth bikes take Total Geometry to the younger rider and give them what they need to become the very best.

Key Spec

- Manitou Machete Air suspension forks
- Shimano Deore 10 speed Gearing
- Tektro hydraulic dis brakes
- Vee Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	66.5	76	520	295	706
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1057	410	30.9	95	331

SKU Part Code	W405V4
Sizes Available	13"
Colour	Matt Moss with Yellow & Olive
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Internal Cable Routing with BBX and Chainstay Post Mount Dropouts
Fork	Manitou Machete , 100mm Travel, Black Alloy Stanchions, Alloy Steerer, Hydro Lockout, Air Spring, Adjustable Rebound
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 28 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Trail 25, Tubeless compatible, 28 Hole
Tyres	VEE TIRE Co, Crown Gem 26" x 2.25"
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M665M, With Clutch, 10 Speed
Cassette	Shimano Deore CS-M4100, 11-42, 10 Speed
Chain	SunRace, 10 Speed
Crankset	Alloy 6061, 28T Narrow Wide Chainring, Single guard, 152mm Crank Length
Bottom Bracket	Square Interface, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 30.9mm x 300mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 30mm Rise, 31.8mm, 680mm Wide
Stem	Whyte Alloy, 35mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Snake
Pump Track
 Colour Option 1



Pump Track bikes need a strong frame - but to be truly great they also need to be light and have geometry that gives the rider perfect control. We'll leave Daryl Brown's riding to tell the rest of the story.

Key Spec

- Suntour XCR 100mm Air Fork
- Whyte 2pc Cranks
- Whyte Custom 35mm rise DJ bars
- Sealed bearing single speed wheelset

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	69	72	595	318	720
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1055 (1075)	385 (405)	30.9	115	331

SKU Part Code	WSNAV1-1
Sizes Available	13"
Colour	Gloss Ice Grey with Black & Gold
Frame	6061 Alloy, Hydro Formed T6 Aluminium, IS Disk Mount, Single Speed Dropouts
Fork	Suntour XCR32-AIR 26" 100mm Travel, Turn Key Lockout
Rear Shock	N/A
Headset	FEIMIN FP-H856B Semi Integrated 11/8" Upper 11/2 Lower Sealed Bearings
Rear Hub	Alloy Double Sealed Single Speed, 14T, 32 Hole
Front Hub	Alloy Double Sealed, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 25mm, 26", Tubeless Compatible, 32 Hole
Tyres	Kenda K-Rad 26" X 2.30, Wire Bead
Shift Levers	N/A
Front Derailleur	N/A
Rear Derailleur	N/A
Cassette	N/A
Chain	KMC, Z1 Anti Drop
Crankset	Whyte Forged 2pcs Cranks 28T, 165mm
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte TILT Post, 6061 Alloy, 30.9mm, 300mm, 2 Bolt Clamp
Seat	Whyte Stubby
Bar	Whyte R35, 6061 Alloy, 35mm Rise, 31.8mm, 720mm Wide
Stem	Whyte Alloy, 35mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M285, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M285, Hydraulic, 160mm Rotor
Brake Levers	Tektro HD-M285
Pedals	Alloy Platform

Snake
Pump Track
 Colour Option 2



Pump Track bikes need a strong frame - but to be truly great they also need to be light and have geometry that gives the rider perfect control. We'll leave Daryl Brown's riding to tell the rest of the story.

Key Spec

- Suntour XCR 100mm Air Fork
- Whyte 2pc Cranks
- Whyte Custom 35mm rise DJ bars
- Sealed bearing single speed wheelset

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
13"	69	72	595	318	720
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
13"	1055 (1075)	385 (405)	30.9	115	331

SKU Part Code	WSNAV1-2
Sizes Available	13"
Colour	Matt Burgundy with Black & Gold
Frame	6061 Alloy, Hydro Formed T6 Aluminium, IS Disk Mount, Single Speed Dropouts
Fork	Suntour XCR32-AIR 26" 100mm Travel, Turn Key Lockout
Rear Shock	N/A
Headset	FEIMIN FP-H856B Semi Integrated 11/8" Upper 11/2 Lower Sealed Bearings
Rear Hub	Alloy Double Sealed Single Speed, 14T, 32 Hole
Front Hub	Alloy Double Sealed, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 25mm, 26", Tubeless Compatible, 32 Hole
Tyres	Kenda K-Rad 26" X 2.30, Wire Bead
Shift Levers	N/A
Front Derailleur	N/A
Rear Derailleur	N/A
Cassette	N/A
Chain	KMC, Z1 Anti Drop
Crankset	Whyte Forged 2pcs Cranks 28T, 165mm
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte TILT Post, 6061 Alloy, 30.9mm, 300mm, 2 Bolt Clamp
Seat	Whyte Stubby
Bar	Whyte R35, 6061 Alloy, 35mm Rise, 31.8mm, 720mm Wide
Stem	Whyte Alloy, 35mm
Grips	Whyte Lock-on V Grip
Front Brakes	Tektro HD-M285, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M285, Hydraulic, 160mm Rotor
Brake Levers	Tektro HD-M285
Pedals	Alloy Platform



Lightweight and responsive, our gravel bikes are perfect for fast paced commutes - and with their proven trail-taming handling they have the edge when the road stops and the real fun begins.

Key Spec

- Light Weight Alloy Flat Mount Gravel Fork
- Shimano GRX 2x10 Compact drivetrain
- Shimano GRX Hydraulic Brakes
- Schwalbe Bite Tubeless Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
48cm	70	74	548	270	756
50cm	70	74	557	270	773
52cm	70	74	566	270	790
54cm	70	74	595	270	807
56cm	70	74	604	270	824
58cm	70	74	623	270	841
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
48cm	1030	435	27.2	115	480
50cm	1040	435	27.2	130	500
52cm	1050	435	27.2	145	520
54cm	1080	435	27.2	160	540
56cm	1090	435	27.2	175	560
58cm	1110	435	27.2	190	580

SKU Part Code	WDEA(size)V2
Sizes Available	48,50,52,54,56,58
Colour	Matt Moss with Olive & Burnt Orange
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Custom Drawn, Chainstay Flat Mount 160mm Disc Mount, BBX Cable Routing
Fork	Whyte Straight Bladed 6061 Alloy, Tapered Alloy Steerer, Internal Cable Routing, Flat Mount Dropouts, 12mm x 100mm Stealth Thru Axle, Eyelets for Mudguards
Rear Shock	N/A
Headset	FEMIMIN H889B, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Thru Axle, Centre-Lock, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Thru Axle, Centre-Lock, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte RG-7, Tubeless Ready, 32 Hole
Tyres	Schwalbe G-ONE BITE, 700 x 40c, TL-Easy with RaceGuard Puncture Protection
Shift Levers	Shimano GRX ST-RX600, 10 Speed
Front Derailleur	Shimano GRX RD-RX400, 10 Speed
Rear Derailleur	Shimano GRX RD-RX400, Shadow Plus, 10 Speed
Cassette	SunRace CSMS1, 11-36, 10 Speed
Chain	SunRace CN10, Black, 10 Speed
Crankset	Whyte, Forged Cranks, 2pcs, Super Compact Double 30-46t, 10 Speed, 170mm
Bottom Bracket	BSA, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Controltech, 6061 Alloy, Gravel/Road compact drop, 10mm riser bar, 31.8mm x 420mm 48cm, 440mm 50cm, 460mm 52&54cm, 480mm 56&58cm
Stem	Whyte Alloy, +-7° Rise, 48/50cm 60mm, 52cm 70mm, 54cm 80mm, 56/58cm 90mm
Grips	Whyte Anti Slip, Cross Bar Tape
Front Brakes	Shimano GRX BR-RX400, 160mm Flat Mount, Internal Routing
Rear Brakes	Shimano GRX BR-RX400, 160mm Flat Mount, Internal Routing
Brake Levers	Shimano GRX ST-RX600, Hydraulic
Pedals	Fibre Reinforced Composite Platform

Friston Gravel



Lightweight and responsive, our gravel bikes are perfect for fast paced commutes - and with their proven trail-taming handling they have the edge when the road stops and the real fun begins.

Key Spec

- Full Carbon tapered straight blade fork
- Remote Access Dropper Seat Post
- SRAM APEX 11 speed Mechanical Gearing
- SRAM APEX Hydraulic Brakes
- Maxxis Rambler Tubeless Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	70	74	559	277	784
52cm	70	74	568	277	801
54cm	70	74	597	277	818
56cm	70	74	606	277	835
58cm	70	74	624	277	852
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	1032	425	30.9	130	500
52cm	1042	425	30.9	145	520
54cm	1072	425	30.9	160	540
56cm	1081	425	30.9	175	560
58cm	1102	425	30.9	190	580

SKU Part Code	WFR(size)V5
Sizes Available	50,52,54,56,58
Colour	Matt Diesel with Light Blue & Slate
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Head Tube, Custom Drawn, Chainstay Flat Mount 160mm Disc Mount, DOX Cable Routing
Fork	Whyte Straight Bladed Full Carbon Fork, Tapered Carbon Steerer, Internal Cable Routing, Flat Mount 180mm Dropouts, 12mm x 100mm Stealth Thru Axle, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 12mm x 142mm Thru Axle, XD Driver, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 12mm x 100mm Thru Axle, 32 Hole, Concealed Hex Key
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis, Rambler TR, 700c x 45c 60TPI EXO Tan Sidewall Protection, Dual Compound
Shift Levers	SRAM Apex 1, Full Hydraulic, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Apex 1, Long Cage, 11 Speed
Cassette	SRAM XG-1150, 10-42, 11 Speed
Chain	SRAM PC-1110, 11 Speed
Crankset	Whyte, Forged 2pcs Cranks, Direct Mount, Narrow/Wide 38T Alloy Chaining, 50/52 170mm, 54 172.5mm, 56/58 175mm 11 Speed
Bottom Bracket	BSA 68mm
Seatpost	Trans-X YSP38 Dropper Post, 30.9mm, 50/52/54 70mm Travel, 56 90mm Travel, 58 110mm Travel, Rocker Remote
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Whyte 500 by Controltech, 6061 Alloy, Gravel 20mm Riser Bar, 31.8mm x 500mm
Stem	Whyte Alloy, +-7° Rise, 50/52cm 60mm, 54cm 70mm, 56/58cm 80mm Extension
Grips	Whyte Anti Slip, Cross Bar Tape
Front Brakes	SRAM Apex 1 Hydraulic, Centre-Lock 180mm Disc, Flat Mount, Internal Routing
Rear Brakes	SRAM Apex 1 Hydraulic, Centre-Lock 160mm Disc, Flat Mount, Internal Routing
Brake Levers	SRAM Apex 1, Hydraulic
Pedals	None

Gisburn

Gravel



Lightweight and responsive, our gravel bikes are perfect for fast paced commutes - and with their proven trail-taming handling they have the edge when the road stops and the real fun begins.

Key Spec

- Full Carbon tapered straight blade fork
- Remote Access Dropper Seat Post
- Shimano GRX 1x11 Drive chain
- Shimano GRX Hydraulic Brakes
- Maxxis Rambler Tubeless Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	70	74	559	277	784
52cm	70	74	568	277	801
54cm	70	74	597	277	818
56cm	70	74	606	277	835
58cm	70	74	624	277	852
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	1032	425	30.9	130	500
52cm	1042	425	30.9	145	520
54cm	1072	425	30.9	160	540
56cm	1081	425	30.9	175	560
58cm	1102	425	30.9	190	580

SKU Part Code	WGIS(size)V5
Sizes Available	50,52,54,56,58
Colour	Gloss Grey with Black & Grey
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Head Tube, Custom Drawn, Chainstay Flat Mount 160mm Disc Mount, DOX Cable Routing
Fork	Whyte Straight Bladed full Carbon Fork, Tapered Carbon Steerer, Internal Cable Routing, Flat Mount 180mm Dropouts, 12mm x 100mm Stealth Thru Axle, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 12mm x 142mm Thru Axle, 28 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, Centre-Lock, 12mm x 100mm Thru Axle, 28 Hole, Concealed Hex Key
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	Easton AR-25, Pinned Joint, Tubeless Ready, 28 Hole
Tyres	Maxxis, Rambler TR, 700c x 45c 60TPI EXO Tan Sidewall Protection, Dual Compound
Shift Levers	SRAM Rival eTAP AXS
Front Derailleur	N/A
Rear Derailleur	SRAM Rival XPLR eTap AXS
Cassette	SRAM XG1251, XPLR, 10-44
Chain	SRAM Rival
Crankset	SRAM Rival 1 Wide, 38T, DUB, 50/52 170mm, 54 172.5mm, 56/58 175mm 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Trans-X YSP38 dropper post, 30.9mm, 50/52/54 70mm Travel, 56 90mm Travel, 58 110mm Travel, Control Lever
Seat	Whyte Custom, Road, Lightweight Foam, CrMo Rails, Triple Panel Design
Bar	Whyte 500 by Controltech, 6061 Alloy, Gravel 20mm Riser Bar, 31.8mm x 500mm
Stem	Whyte Alloy, +-7° Rise, 50/52cm 60mm, 54cm 70mm, 56/58cm 80mm, Extension
Grips	Whyte Anti Slip, Cross Bar Tape
Front Brakes	SRAM Rival, 180mm CentreLine Rotor, Centre Lock
Rear Brakes	SRAM Rival, 160mm CentreLine, Centre Lock
Brake Levers	SRAM Rival
Pedals	None



Lightweight and responsive, our gravel bikes are perfect for fast paced commutes - and with their proven trail-taming handling they have the edge when the road stops and the real fun begins.

Key Spec

- Light Weight Alloy Flat Mount Gravel Fork
- SRAM APEX 11 speed Mechanical Gearing
- SRAM APEX Hydraulic Brakes
- Maxxis Receptor Tubeless Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
50cm	70	74	557	265	768
52cm	70	74	566	265	785
54cm	70	74	595	265	802
56cm	70	74	604	265	819
58cm	70	74	623	265	836
58cm	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
50cm	1040	435	27.2	130	500
52cm	1050	435	27.2	145	520
54cm	1080	435	27.2	160	540
56cm	1090	435	27.2	175	560
58cm	1110	435	27.2	190	580

SKU Part Code	WGLE(size)V5
Sizes Available	50,52,54,56,58
Colour	Matt Moss with Gold & Heather
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, SCR, Tapered Head Tube, Custom Drawn, Chainstay Flat Mount 160mm Disc Mount, DOX Cable Routing
Fork	Whyte Straight Bladed 6061 Alloy, Tapered Alloy Steerer, Internal Cable Routing, Flat Mount Dropouts, 12mm x 100mm Stealth Thru Axle, Eyelets for Mudguards
Rear Shock	N/A
Headset	FSA No. 42, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 142mm Thru Axle, Centre-Lock, 32 Hole, concealed hex key
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Thru Axle, Centre-Lock, 32 Hole, Concealed Hex Key
Spokes	DT Swiss New Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i25 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis, Receptor TR, 650b x 47c, 120 Tpi, EXO Tan Sidewall Protection
Shift Levers	SRAM Apex 1, Full Hydraulic, 11 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM Apex 1, Long Cage, 11 Speed
Cassette	SunRace CSMS8, 11-42, 11 Speed
Chain	KMC X11, Black/Silver, 11 Speed
Crankset	Whyte, Forged Cranks, Direct Mount 42T Narrow Wide Chainring, 11 Speed
Bottom Bracket	BSA, Cartridge Bearings, 73mm
Seatpost	Whyte 6061 Alloy, 15mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Light Weight Triple Density Base, Triple Panel Design
Bar	Controltech, 6061 Alloy, Gravel/Road compact drop, 10mm riser bar, 31.8mm x 440mm 50cm, 500mm 52/54/56/58cm
Stem	Whyte Alloy, +-7° Rise, 50cm 60mm, 52cm 70mm, 54cm 80mm, 56/58cm 90mm Extension
Grips	Whyte Anti Slip, Cross Bar Tape
Front Brakes	SRAM Apex 1 Hydraulic, Centre-Lock 160mm Disc, Flat Mount, Internal Routing
Rear Brakes	SRAM Apex 1 Hydraulic, Centre-Lock 160mm Disc, Flat Mount, Internal Routing
Brake Levers	SRAM Apex 1, Hydraulic
Pedals	None

Whitechapel

Commuter



Light, nimble, comfortable and fast - that's what we set out to achieve. And we think we hit the nail on the head. Perfect for café runs, pub lunches or the commute to work - they do it all.

Key Spec

- Light Weight Alloy Fork
- Microshift 1x9 speed Mechanical Gearing
- Tektro M275 Brakes
- Vittoria Terreno Zero Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	73.5	595.2	268	750
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533

SKU Part Code	WWH(size)V4
Sizes Available	M,L,XL
Colour	Matt Granite with Grey & Black
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts, Chain Stay Kick Stand Mount
Fork	Whyte Straight Bladed 6061 Alloy, Forged Crown, Alloy Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FEIMIN H809C, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 23mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 32 Hole Front
Tyres	Vittoria Terreno Zero 700 x 37c, Puncture Protection
Shift Levers	Microshift SL-M859-R, Trigger Shifter, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M46S, 9 Speed
Cassette	Microshift CS-H092, 11-36, 9 Speed
Chain	Sunrace, 9 Speed
Crankset	Alloy, 42T Chainring with Alloy Chain Guard
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 25mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L/XL 60mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Carnaby Compact Commuter



Light, nimble, comfortable and fast - that's what we set out to achieve. And we think we hit the nail on the head. Perfect for café runs, pub lunches or the commute to work - they do it all.

Key Spec

- Lightweight Tapered Alloy Fork
- Microshift 10 speed Mechanical Gearing
- Tektro M275 Brakes
- Vittoria Terreno Zero Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
M	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1049.5	430	27.2	140	393.7
M	1067.4	430	27.2	160	431.8
L	1078.4	430	27.2	180	469.9

SKU Part Code	WCAR(size)V4
Sizes Available	S,M,L
Colour	Matt Diesel with Aqua & Mint
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX and Custom Whyte Dropouts, Chain Stay Kick Stand Mount
Fork	Whyte Straight Bladed 6061 Alloy, Forged Crown, Alloy Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FEIMIN H809C, Integrated Road, 1 1/8" Sealed Cartridge Bearings, 41mm Diameter
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 23mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 32 Hole Front
Tyres	Vittoria Terreno Zero 700 x 37c, Puncture Protection
Shift Levers	Microshift SL-M859-R, Trigger Shifter, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M46S, 9 Speed
Cassette	Microshift CS-H092, 11-36, 9 Speed
Chain	Sunrace, 9 Speed
Crankset	Alloy, 40T Chainring with Alloy Chain Guard
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 25mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Shoreditch

Commuter



Light, nimble, comfortable and fast - that's what we set out to achieve. And we think we hit the nail on the head. Perfect for café runs, pub lunches or the commute to work - they do it all.

Key Spec

- Light Weight Tapered Alloy Fork
- Microshift 10 speed Mechanical Gearing
- Tektro M275 Brakes
- Vittoria Terreno Zero Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	73.5	595.2	268	750
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533

SKU Part Code	WSH(size)V3
Sizes Available	M,L,XL
Colour	Matt Olive with Khaki & Burnt Orange
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Internal Cable Routing with BBX and Custom Whyte Dropouts, Chain Stay Kick Stand Mount
Fork	Whyte Straight Bladed 6061 Alloy, Alloy Tapered Steerer, Internal Cable Routing, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FEIMIN H889TN, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 23mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 32 Hole Front
Tyres	Vittoria Terreno Zero 700 x 37c, Puncture Protection
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M4120-SGS, Shadow Plus, 10 Speed
Cassette	Shimano Deore CS-M4100, 11-42, 10 Speed
Chain	Sunrace, 10 Speed
Crankset	2pcs Alloy, Narrow/Wide 42T Chaining with Guard, 10 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 25mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L/XL 60mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Portobello

Commuter



Light, nimble, comfortable and fast - that's what we set out to achieve. And we think we hit the nail on the head. Perfect for café runs, pub lunches or the commute to work - they do it all.

Key Spec

- Light Weight Tapered Alloy Fork with 12mm Axle
- Microshift 10 speed Mechanical Gearing
- Clarks Clout Brakes
- WTB Road Plus Horizon Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	73.5	595.2	268	750
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533

SKU Part Code	WPO(size)V4
Sizes Available	M,L,XL
Colour	Matt Bronze with Copper & Burnt Orange
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Internal Cable Routing with BBX and Custom Whyte Dropouts, Chain Stay Kick Stand Mount
Fork	Whyte Straight Bladed 6061 Alloy, Alloy Tapered Steerer, Internal Cable Routing, 12mm Thru Axle, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FEIMIN H889TN, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Thru Axle, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road Plus 650b, Low Profile, 25mm Wide, Tubeless Compatible, 32 Hole Rear and 32 Hole Front
Tyres	WTB Horizon 650b x 47c, Tan Wall, Road Plus
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M66M, 10 Speed
Cassette	Microshift CS-H103A, 11-42, 10 Speed
Chain	Sunrace, 10 Speed
Crankset	2pcs Alloy, Narrow/Wide 42T Chainring with Guard, 10 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L/XL 60mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Clarks CLOUT-1, Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Clarks CLOUT-1, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Clarks CLOUT-1
Pedals	Fibre Reinforced Composite Platform

Victoria Compact Commuter



Light, nimble, comfortable and fast - that's what we set out to achieve. And we think we hit the nail on the head. Perfect for café runs, pub lunches or the commute to work - they do it all.

Key Spec

- Light Weight Tapered Alloy Fork with 12mm Axle
- Microshift 10 speed Mechanical Gearing
- Clarks Clout Brakes
- WTB Road Plus Horizon Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
M	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1049.5	430	27.2	140	393.7
M	1067.4	430	27.2	160	431.8
L	1078.4	430	27.2	180	469.9

SKU Part Code	WV(size)V4
Sizes Available	S,M,L
Colour	Matt Burnt Orange with Earth & Grey
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Internal Cable Routing with BBX and Custom Whyte Dropouts, Chain Stay Kick Stand Mount
Fork	Whyte Straight Bladed 6061 Alloy, Alloy Tapered Steerer, Internal Cable Routing, 12mm Thru Axle, Post Mount with Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FEIMIN H889TN, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Thru Axle, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road Plus 650b, Low Profile, 25mm Wide, Tubeless Compatible, 32 Hole Rear and 32 Hole Front
Tyres	WTB Horizon 650b x 47c, Tan Wall, Road Plus
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M66M, 10 Speed
Cassette	Microshift CS-H103A, 11-42, 10 Speed
Chain	Shimano HG54, 10 Speed
Crankset	2pcs Alloy, Narrow Wide 40T Chainring with Guard, 10 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Clarks CLOUT-1, Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Clarks CLOUT-1, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Clarks CLOUT-1
Pedals	Fibre Reinforced Composite Platform



Light, nimble, comfortable and fast - that's what we set out to achieve. And we think we hit the nail on the head. Perfect for café runs, pub lunches or the commute to work - they do it all.

Key Spec

- Light Weight Tapered Carbon Fork
- Microshift XLE 11 speed Mechanical Gearing
- Shimano MT-400 Brakes
- Vittoria Terreno Zero Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	73.5	595.2	268	750
L	70	73	613	271.5	786
XL	70	73	626.9	271.5	817
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1078.4	430	27.2	165	444.5
L	1094.3	430	27.2	185	495
XL	1109.3	430	27.2	205	533

SKU Part Code	WST(size)V3
Sizes Available	M,L,XL
Colour	Gloss Moss with Silver & Black
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Internal Cable Routing with BBX and Custom Whyte Dropouts, Chain Stay Kick Stand Mount
Fork	Whyte Straight Bladed full carbon Tapered Steerer, Internal Cable Routing, Internal Cable Routing, 12mm Thru Axle, Flat Mountn160mm Adaptor, Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FEIMIN H889TN, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Thru Axle, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 23mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 32 Hole Front
Tyres	Vittoria Terreno Zero 700 x 37c, Folding, Puncture Protection
Shift Levers	Shimano Deore SL-M5100, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5100-SGS, 11 Speed
Cassette	Microshift CS-H113, 11-46, 11 Speed
Chain	SunRace, 11 Speed
Crankset	2pcs Alloy, Narrow/Wide 42T Chainring with Guard, 11 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 2014 Alloy, 20mm Offset, 27.2mm x S/M/L 350mm, XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm, XL 70mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Shimano MT400, Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Shimano MT400, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Shimano MT400
Pedals	Fibre Reinforced Composite Platform

Pimlico Compact Commuter



Light, nimble, comfortable and fast - that's what we set out to achieve. And we think we hit the nail on the head. Perfect for café runs, pub lunches or the commute to work - they do it all.

Key Spec

- Light Weight Tapered Carbon Fork
- Microshift XLE 11 speed Mechanical Gearing
- Shimano MT-400 Brakes
- Vittoria Terreno Zero Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	547.9	266.5	732.5
M	69.5	73.5	573.6	266.5	735.5
L	70	73	599.8	266.5	767.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1049.5	430	27.2	140	393.7
M	1067.4	430	27.2	160	431.8
L	1078.4	430	27.2	180	469.9

SKU Part Code	WPI(size)V3
Sizes Available	S,M,L
Colour	Matt Midnight with Grey & Magenta
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Tapered Head Tube, Internal Cable Routing with BBX and Custom Whyte Dropouts, Chain Stay Kick Stand Mount
Fork	Whyte Straight Bladed full carbon Tapered Steerer, Internal Cable Routing, Internal Cable Routing, 12mm Thru Axle, Flat Mountn160mm Adaptor, Single Eyelets for Mudguards
Rear Shock	N/A
Headset	FEIMIN H889TN, Integrated Road, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 100mm Thru Axle, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte Disc Road, Low Profile, 23mm Wide, Tubeless Compatible, 3M Reflective Decals, 32 Hole Rear and 32 Hole Front
Tyres	Vittoria Terreno Zero 700 x 37c, Folding, Puncture Protection
Shift Levers	Shimano Deore SL-M5100, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M665M, 11 Speed
Cassette	Microshift CS-H113, 11-46, 11 Speed
Chain	SunRace, 11 Speed
Crankset	2pcs Alloy, Narrow/Wide 42T Chainring with Guard, 11 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 2014 Alloy, 20mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, S 45mm, M/L 60mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Shimano MT400, Hydraulic, 160mm Rotor, Internal Routing
Rear Brakes	Shimano MT400, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Shimano MT400
Pedals	Fibre Reinforced Composite Platform



We use everything we've learned building benchmark MTB hardtails to create a remarkably capable, stable and fast hybrid - sure to expand the leisure cyclist's horizons from city centre to cycle paths and beyond.

Key Spec

- Suntour NEX Coil 63mm Forks
- Microshift ADVENT 1x9 speed Mechanical Gearing
- Tektro M275 Brakes
- Schwalbe Road Cruiser Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	592	278	765
M	69	73.5	617	278	774
L	69	73	632	278	805
XL	69	73	646.6	278	854
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1099	435	30.9	115	457
M	1119	435	30.9	125	495
L	1129	435	30.9	135	546
XL	1144	435	30.9	145	585

SKU Part Code	WRI(size)V4
Sizes Available	S,M,L,XL
Colour	Matt Zinc with Moss & Rose
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NEX HLO 63mm Travel, Hydro Lockout
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 23 x 700c, 32 hole
Tyres	Schwalbe Road Cruiser TOUR, 700 x 40c, Green Compound, K-Guard Puncture Protection
Shift Levers	Microshift SL-M819R, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M619M, 9 Speed
Cassette	Microshift CS-H093, 11-46, 9 Speed
Chain	SunRace, 9 Speed
Crankset	Whyte Forged, 3pcs Alloy, Narrow/Wide 42T Chainring with Guard, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, +6 Degree, 70mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Ridgeway Women's Leisure



We use everything we've learned building benchmark MTB hardtails to create a remarkably capable, stable and fast hybrid - sure to expand the leisure cyclist's horizons from city centre to cycle paths and beyond.

Key Spec

- Suntour NEX Coil 63mm Forks
- Microshift ADVENT 1x9 speed Mechanical Gearing
- Tektro M275 Brakes
- Schwalbe Road Cruiser Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	570	278	718
M	69	74	587	278	737
L	69	73.5	612	278	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1081.3	435	30.9	107	431.8
M	1094	435	30.9	115	457
L	1114	435	30.9	125	495

SKU Part Code	WRIL(size)V4
Sizes Available	S,M,L
Colour	Matt Burnt Orange with Earth & Grey
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NEX HLO 63mm Travel, Hydro Lockout
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 23 x 700c, 32 hole
Tyres	Schwalbe Road Cruiser TOUR, 700 x 40c, Green Compound, K-Guard Puncture Protection
Shift Levers	Microshift SL-M819R, 9 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M619M, 9 Speed
Cassette	Microshift CS-H093, 11-46, 9 Speed
Chain	SunRace, 9 Speed
Crankset	Whyte Forged, 3pcs Alloy, Narrow/Wide 42T Chainring with Guard, 9 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, +6 Degree, 70mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform



We use everything we've learned building benchmark MTB hardtails to create a remarkably capable, stable and fast hybrid - sure to expand the leisure cyclist's horizons from city centre to cycle paths and beyond.

Key Spec

- Suntour NCX Coil 63mm Light Forks
- Shimano Deore 10 speed Mechanical Gearing
- Tektro M275 Brakes
- Schwalbe Road Cruiser Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	592	278	765
M	69	73.5	617	278	774
L	69	73	632	278	805
XL	69	73	646.6	278	854
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1099	435	30.9	115	457
M	1119	435	30.9	125	495
L	1129	435	30.9	135	546
XL	1144	435	30.9	145	585

SKU Part Code	WMA(size)V3
Sizes Available	S,M,L,XL
Colour	Matt Granite with Silver & Grey
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Steel Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 23 x 700c, 32 hole
Tyres	Schwalbe Road Cruiser TOUR, 700 x 40c, Green Compound, K-Guard Puncture Protection
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5020-SGS, Shadow Plus, 10 Speed /Microshift RD-M665M, With Clutch, 10 Speed
Cassette	SunRace CSMS2, 11-46, 10 Speed
Chain	SunRace, 10 Speed
Crankset	Alloy Narrow/Wide 40T Chainring with Guard, 10 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L/XL 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, +6 Degree, 70mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform

Malvern Women's Leisure



We use everything we've learned building benchmark MTB hardtails to create a remarkably capable, stable and fast hybrid - sure to expand the leisure cyclist's horizons from city centre to cycle paths and beyond.

Key Spec

- Suntour NCX Coil 63mm Light Forks
- Shimano Deore 10 speed Mechanical Gearing
- Tektro M275 Brakes
- Schwalbe Road Cruiser Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	570	278	718
M	69	74	587	278	737
L	69	73.5	612	278	756.9

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1081.3	435	30.9	107	431.8
M	1094	435	30.9	115	457
L	1114	435	30.9	125	495

SKU Part Code	WMAL(size)V3
Sizes Available	S,M,L
Colour	Matt Diesel with Light Blue & Mint
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Steel Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 23 x 700c, 32 hole
Tyres	Schwalbe Road Cruiser TOUR, 700 x 40c, Green Compound, K-Guard Puncture Protection
Shift Levers	Shimano Deore SL-M4100, 10 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano Deore RD-M5020-SGS, Shadow Plus, 10 Speed /Microshift RD-M665M, With Clutch, 10 Speed
Cassette	SunRace CSMS2, 11-46, 10 Speed
Chain	SunRace, 10 Speed
Crankset	Alloy Narrow/Wide 40T Chainring with Guard, 10 Speed
Bottom Bracket	Square Interface, Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, +6 Degree, 70mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor
Rear Brakes	Tektro HD-M275, Hydraulic, 160mm Rotor, Internal Routing
Brake Levers	Tektro HD-M275
Pedals	Fibre Reinforced Composite Platform



We use everything we've learned building benchmark MTB hardtails to create a remarkably capable, stable and fast hybrid - sure to expand the leisure cyclist's horizons from city centre to cycle paths and beyond.

Key Spec

- Suntour NCX Coil 63mm Light Forks
- Microshift XLE 11 speed Mechanical Gearing
- Shimano MT-200 Brakes
- Schwalbe Road Cruiser Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74	592	278	765
M	69	73.5	617	278	774
L	69	73	632	278	805
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1099	435	30.9	115	457
M	1119	435	30.9	125	495
L	1129	435	30.9	135	546

SKU Part Code	WCA(size)V4
Sizes Available	S,M,L
Colour	Matt Bronze with Silver & Copper
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX, Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 23 x 700c, 32 hole
Tyres	Schwalbe Road Cruiser TOUR, 700 x 40c, Green Compound, K-Guard Puncture Protection
Shift Levers	Shimano Deore SL-M5100, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M665M, 11 Speed
Cassette	Microshift CS-H113, 11-46, 11 Speed
Chain	SunRace, 11 Speed
Crankset	Alloy Narrow/Wide 40T Chainring with Guard, 11 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x S/M 350mm, L 400mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, +6 Degree, 70mm
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano MT400, Hydraulic, 160mm Rotor S/M / Clarks CLOUT Hydraulic 160mm Rotor L/XL
Rear Brakes	Shimano MT400, Hydraulic, 160mm Rotor, Internal, S/M / Clarks CLOUT Hydraulic 160mm Rotor Internal, L/XL
Brake Levers	Shimano MT400 / Clarks CLOUT Hydraulic
Pedals	Fibre Reinforced Composite Platform



We use everything we've learned building benchmark MTB hardtails to create a remarkably capable, stable and fast hybrid - sure to expand the leisure cyclist's horizons from city centre to cycle paths and beyond.

Key Spec

- Suntour NCX Coil 63mm Light Forks
- Microshift XLE 11 speed Mechanical Gearing
- Shimano MT-200 Brakes
- Schwalbe Road Cruiser Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	68	74.5	570	278	718
M	69	74	587	278	737
L	69	73.5	612	278	756.9
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1081.3	435	30.9	107	431.8
M	1094	435	30.9	115	457
L	1114	435	30.9	125	495

SKU Part Code	WCAL(size)V4
Sizes Available	S,M,L
Colour	Matt Midnight with Silver & Dark Red
Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Internal Cable Routing with BBX , Custom Whyte Dropouts and Integrated Kickstand Mount
Fork	SR Suntour NCX-D LO, 63mm Travel, Alloy Steerer, Hydro Lockout
Rear Shock	N/A
Headset	FEIMIN H807B, Semi Integrated, 1 1/8" Lower 1 1/2 Lower Caged Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, PG, Black Stainless, Brass Nipples
Rims	Whyte 23 x 700c, 32 hole
Tyres	Schwalbe Road Cruiser TOUR, 700 x 40c, Green Compound, K-Guard Puncture Protection
Shift Levers	Shimano Deore SL-M5100, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Microshift RD-M665M, 11 Speed
Cassette	Microshift CS-H113, 11-46, 11 Speed
Chain	SunRace, 11 Speed
Crankset	Alloy Narrow/Wide 40T Chainring with Guard, 11 Speed
Bottom Bracket	Sealed Cartridge Bearings, 68mm
Seatpost	Whyte 6061 Alloy, 12mm Offset, 30.9mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Compact Fit
Bar	Whyte 6061 Alloy, 25mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy, +6 Degree, 70mm
Grips	Whyte Custom Ergo Dual Density Lock-on
Front Brakes	Shimano MT400, Hydraulic, 160mm Rotor S/M / Clarks CLOUT Hydraulic 160mm Rotor L/XL
Rear Brakes	Shimano MT400, Hydraulic, 160mm Rotor, Internal, S/M / Clarks CLOUT Hydraulic 160mm Rotor Internal, L/XL
Brake Levers	Shimano MT400 / Shimano MT400 / Clarks CLOUT Hydraulic
Pedals	Fibre Reinforced Composite Platform

Coniston e-Bike

e-Leisure



The Coniston has you covered with its stylish, lightweight comfort. This is riding and exploring made easy – from the daily commute to weekends away.

Key Spec

- Shimano E5000 and 418Wh battery
- Suntour NEX suspension fork - Coil
- Shimano XT/Zee 10 speed Mechanical Gearing
- Tektro Hydraulic Brakes
- Schwalbe Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	66	73.5	625	273.5	776
L	66	73	650	273.5	806
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1172	458	30.9	125	444.5
L	1192	458	30.9	135	495.3

SKU Part Code	WCON(size)V2
Sizes Available	M,L
Colour	Matt Granite with Grey & Blue
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
Fork	SR Suntour NEX-E25 NLO DS, 63mm Travel, Tapered Steerer Tube, Coil Spring
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte T-23 x 700c, 32 hole, with eyelets
Tyres	Schwalbe Road Cruiser Tour Green Compound, 700 x 47c, with K-Guard Puncture Protection
Shift Levers	Shimano SL-M640, Zee, 10 Speed with STEPS SC-E5000 Display
Front Derailleur	N/A
Rear Derailleur	Shimano RD-M781, Deore XT, SGS 10-Speed, Shadow
Cassette	Sunrace CSMS1, 11-36, 10 Speed
Chain	KMC e10T, e-bike specific chain with EPT Anti-Rust, 10 Speed
Crankset	Whyte Forged 44T with Double Sided Chain Guard, 165mm, 10 Speed
Bottom Bracket	N/A
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9 x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
Stem	Whyte Alloy 6061, 70mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-T280, 160mm Disc, Post Mount, Internal Routing
Rear Brakes	Tektro HD-T280, 160mm Disc, Internal Routing
Brake Levers	Tektro HD-T280 2 Finger, Black
Pedals	Fibre Reinforced Composite Platform

Coniston Women's e-Bike

e-Leisure



The Coniston has you covered with its stylish, lightweight comfort. This is riding and exploring made easy – from the daily commute to weekends away.

Key Spec

- Shimano E5000 and 418Wh battery
- Suntour NEX suspension fork - Coil
- Shimano XT/Zee 10 speed Mechanical Gearing
- Tektro Hydraulic Brakes
- Schwalbe Tyres

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66	74.5	581	273.5	677
M	66	74	605	273.5	691
L	66	73.5	630	273.5	702
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1137	458	30.9	107	406.4
M	1157	458	30.9	115	444.5
L	1177	458	30.9	125	495.3

SKU Part Code	WCONL(size)V2
Sizes Available	S,M,L
Colour	Matt Granite with Silver & Magenta
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
Fork	SR Suntour NEX-E25 NLO DS, 63mm Travel, Tapered Steerer Tube, Coil Spring
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, 1 1/2" Lower and 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	Whyte T-23 x 700c, 32 hole, with eyelets
Tyres	Schwalbe Road Cruiser Tour Green Compound, 700 x 47c, with K-Guard Puncture Protection
Shift Levers	Shimano SL-M640, Zee, 10 Speed with STEPS SC-E5000 Display
Front Derailleur	N/A
Rear Derailleur	Shimano RD-M781, Deore XT, SGS 10-Speed, Shadow
Cassette	Sunrace CSMS1, 11-36, 10 Speed
Chain	KMC e10T, e-bike specific chain with EPT Anti-Rust, 10 Speed
Crankset	Whyte Forged 44T with Double Sided Chain Guard, 165mm, 10 Speed
Bottom Bracket	N/A
Seatpost	Whyte 6061 Alloy, 15mm Offset, 30.9mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Alloy 6061, 31.8mm, 20mm Rise, 620mm Wide
Stem	Whyte Alloy 6061, 70mm
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-T280, 160mm Disc, Post Mount, Internal Routing
Rear Brakes	Tektro HD-T280, 160mm Disc, Internal Routing
Brake Levers	Tektro HD-T280 2 Finger, Black
Pedals	Fibre Reinforced Composite Platform

Clifton e-Bike

e-Commuter



Built to explore, the Clifton and Highgate bring elegant style and class. With full mudguards, rack and lights you have everything you need for adventure or your daily commute – and you'll look good doing it.

Key Spec

- Shimano E5000 and 418Wh battery
- Shimano XT/Zee 10 speed Mechanical Gearing
- Tektro Hydraulic Brakes
- WTB Byway Tyres
- Fully equipped, lights rack, mudguards and suspension seatpost

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	70	74	600	265	755
L	70	74	614	265	791
XL	70	74	634	265	822
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1095	450	27.2	165	445.3
L	1110	450	27.2	185	495.3
XL	1125	450	27.2	205	533.4

SKU Part Code	WCL(size)V2
Sizes Available	M,L,XL
Colour	Matt Granite with Silver & Blue
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand Mount
Fork	Whyte Straight Bladed 6061 Alloy, Flat Mount, Single Eyelets for Mudguards and Internal Cable Routing
Rear Shock	N/A
Headset	FSA No. 42 B CUP for 1 1/2" Lower and 1 1/8" Upper
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB STp i23 650b Rims with TCS System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	WTB Byway, Tan Wall, 650 x 47c
Shift Levers	Shimano SL-M640, Zee, 10 Speed with STEPS SC-E5000 Display
Front Derailleur	N/A
Rear Derailleur	Shimano RD-M781, Deore XT, SGS 10-Speed, Shadow
Cassette	Sunrace CSMS1, 11-36, 10 Speed
Chain	KMC e10T, e-bike specific chain with EPT Anti-Rust, 10 Speed
Crankset	Whyte Forged 44T with Double Sided Chain Guard, 165mm, 10 Speed
Bottom Bracket	N/A
Seatpost	Whyte Suspension Seat Post 6061 Alloy, 12mm Offset, 27.2mm x 350mm, 2 Bolt Clamp
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Alloy 6061, 31.8mm, 25mm Rise, 620mm Wide
Stem	Whyte Alloy 6061, 70mm,
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-R280, 160mm Disc, Flat Mount, Internal Routing
Rear Brakes	Tektro HD-T280, 160mm Disc, Internal Routing
Brake Levers	Tektro 2 Finger Black
Pedals	Fibre Reinforced Composite Platform

Highgate Compact e-Bike

e-Commuter



Built to explore, the Clifton and Highgate bring elegant style and class. With full mudguards, rack and lights you have everything you need for adventure or your daily commute – and you'll look good doing it.

Key Spec

- Shimano E5000 and 418Wh battery
- Shimano XT/Zee 10 speed Mechanical Gearing
- Tektro Hydraulic Brakes
- WTB Byway Tyres
- Fully equipped, lights rack, mudguards and suspension seatpost

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	69	74.5	553	265	720
M	69.5	73.5	579	265	741
L	70	73	605	265	774
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1067	450	27.2	140	393.7
M	1078	450	27.2	160	431.8
L	1095	450	27.2	180	469.9

SKU Part Code	WHIG(size)V2
Sizes Available	S,M,L
Colour	Matt Granite with Silver & Magenta
Frame	6061 Hydro Formed T6 Aluminium, Tapered Head Tube, Hydro Formed Down Tube, Custom Drawn, Multi Butted with Custom Whyte Dropouts and Kick Stand mount
Fork	Whyte Straight Bladed 6061 Alloy, Flat Mount, Single Eyelets for Mudguards and Internal Cable Routing
Rear Shock	N/A
Headset	FSA No. 42 B CUP for 1 1/2" Lower and 1 1/8" Upper
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 32 Hole
Spokes	2.0mm, Black Stainless with Brass Nipples
Rims	WTB STp i23 650b Rims with TCS System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	WTB Byway, Tan Wall, 650 x 47c
Shift Levers	Shimano SL-M640, Zee, 10 Speed with STEPS SC-E5000 Display
Front Derailleur	N/A
Rear Derailleur	Shimano RD-M781, Deore XT, SGS 10-Speed, Shadow
Cassette	Sunrace CSMS1, 11-36, 10 Speed
Chain	KMC e10T, e-bike specific chain with EPT Anti-Rust, 10 Speed
Crankset	Whyte Forged 44T with Double Sided Chain Guard, 165mm, 10 Speed
Bottom Bracket	N/A
Seatpost	Whyte Suspension 6061 Alloy, 12mm Offset, 30.9mm, 2 Bolt Clamp
Seat	Whyte Custom
Bar	Whyte 6061 Alloy, 20mm Rise, 31.8mm, 620mm Wide
Stem	Whyte Alloy 6061, 70mm Extension
Grips	Whyte Custom Dual Density Lock-on
Front Brakes	Tektro HD-R280, 160mm Disc, Flat Mount, Internal Routing
Rear Brakes	Tektro HD-T280, 160mm Disc, Internal Routing
Brake Levers	Tektro
Pedals	Fibre Reinforced Composite Platform